



Acco Chain & Lifting Products Division

Issued 2-19-88
Supersedes 10-1-85

30-1

WORK-RATED®

WIRE ROPE ELECTRIC HOISTS
CAPACITIES 1 to 20 TONS

Wright family of "Work-rated" hoists is a complete line of electric wire rope hoists. It is an advanced design incorporating the most recent materials and concept. The most current duty cycle and safety requirements of users are built into this line, not added on.

CONSTRUCTION FEATURES:

CONTROLS: Choose from single-, 2-speed or 5-step variable speed. Controls are magnetic reversing type, mechanically and electrically interlocked with 115 control circuit. All wiring conforms to applicable NEC and CSA requirements. Included are time delay fuses for branch circuit overcurrent protection and motor running overcurrent protection. NEMA Type 3R enclosures are standard. Cover is light-weight, tough ABS material, deep-drawn for maximum control accessibility.

MOTOR: Standard NEMA flange Class F insulation, 30-minute duty motor is provided for standard commercial power supplies. The motor has a standard NEMA shaft extension.

GEAR TRAIN: Quiet, compact helical gearing and external spur drum gear are enclosed in the same oil-tight housing. All gearing is machine cut, heat-treated alloy steel with shock-resistant ductile cores. Gearing is designed to AGMA standards for maximum life, and operates in an oil bath. Rugged aluminum alloy housing provides rapid heat dissipation.

BEARINGS: Precision heavy-duty ball bearings support all shafts. All bearings are either splash lubricated, or lifetime pre-lubricated and sealed.

DRUM: The large diameter steel drum has deep machined grooves and large flanges. At least two full turns of rope remain on the drum at the lowest hook position of rated lift.


HOOK: Drop forged heat-treated steel hook swivels 360° on a shielded roller thrust bearing. Spring latch is standard.

WIRE ROPE: Either improved plow steel with fiber center or XIP (extra improved plow) steel with steel center is supplied, depending on hoist capacity. Both are preformed. Swaged fittings are supplied at both ends.

MECHANICAL LOAD BRAKE: Automatic Weston-type multiple disc brake can hold a full capacity load independent of motor brake. This brake assures that load does not accelerate while being lowered. No wear compensation adjustment is required.

MOTOR BRAKE: Rectified d-c magnet-actuated disc brake has been proved in millions of hours of in-service operation. It delivers rapid stops with minimum or zero hook drift. Series 3200000 thru 3500000 hoist have aluminum alloy brake cover with fins; and brake is separated from gear housing for rapid cooling. This multiple coil brake is rated a minimum of 150% of full load motor torque.

Series 3200000 thru 3500000 hoist also have an exclusive brake-sensing switch that prevents the motor from operating against the brake should brake adjustment be necessary.



LIMIT SWITCH: A gravity-type upper hook travel limit switch provided. The unit is equipped with an automatic momentary lowering circuit. An optional geared limit switch which can be factory or field mounted is also available.

OVERLOAD CUTOFF: Exclusive patented Wright unit is standard on all Work-rated hoists except single-line models.

The Overload Cutoff is a protective device that will permit operation of the hoist within its rated capacity, but will prevent lifting of suspended loads which could cause damage to a properly maintained hoist. In operation it interrupts the raising circuit to the hoist motor and resets automatically when the overload is removed.


WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

HOW TO SPECIFY A *Work-rated* HOIST


1. DETERMINE THE CAPACITY, LIFTING SPEED AND LIFTING DISTANCE.

2. SPECIFY HOIST SERVICE CLASSIFICATION. *Wright* electric hoists are *Work-rated* according to their designed capabilities to provide the user with maximum performance for minimum maintenance and down time. See Master Catalog Section 60-1 through 60-8 for performance specifications.


3. DETERMINE THE REEVING REQUIRED FOR YOUR APPLICATION. *Work-rated* hoists may be reeved in various ways to gain desired mechanical advantages ... capacity, lifting distance, and lifting speeds.




2 PS
2 Part Single




4 PS
4 Part Single



2 PD
2 Part Double



4 PD (a)
4 Part Double
Product Series 32
through 35




4 PD (a)
4 Part Double
Product Series 36

Reeving terminology is either "single" or "double" which refers to the number of wire ropes coming from the drum.

Another word "part" refers to the mechanical advantage gained by multiple reeving. For example, with 2 part single reeving (2PS) the load is distributed over the two parts and mechanical advantage doubles the capacity of one part reeving and reduces by one half the lifting or lowering speed of the hook.

Reeving changes hoist arrangement to the beam or track, minimum headroom distance, and lateral hook travel.


(a) 4 PD Reeving shown does not apply to the *WRIGHT AMERICAN* hoist.



	Standard Headroom Parallel Mounted	Close Headroom Parallel Mounted	Close Headroom Cross Mounted
Reeving:	2 PS or 4 PS	2 PD	2 PD or 4 PD
Minimum Headroom:	Fair	Good	Best
Lateral Hook Travel:	Hook travels	None	None
Cost:	Lower	Low	High

HEADROOM: Some applications require that the distance from the bottom of beam to saddle of the hook be held to a minimum. This dimension will determine whether a standard or close headroom is required.

LATERAL HOOK TRAVEL:



Some applications require that the load, when being lifted, not move right or left from hoist centerline. If this requirement is known, a true vertical lift hoist must be used. These are described as two part double (2PD) or four part double (4PD) and are available in both parallel or cross mounted hoists.



4. SPECIFY PROPER PRODUCT NUMBER in regard to hoist.

Capacity, lifting speed, suspension and hoist control are found in the following pages.

5. "TOP VALUE" HOISTS SHOULD BE CHECKED FIRST. The best priced hoists are the "Top Value" models which are selected hoists in popular capacities, lifts, and speeds, and are available in all suspensions.

The "Top Value" hoist product numbers in following pages are identified with white numbers and dark blue background.

6. SPECIFY MOTOR VOLTAGE: *Wright* standard motors are available in 200/230/460/575-3-60 power with Class B insulation, and are totally enclosed non-ventilated. Control is furnished as standard equipment. Additional motor and control accessories and modifications are found in Section 35 in "C Motor" and "D Controllers" subdivisions.

7. SPECIFY BEAM FLANGE WIDTH:

FOR PRODUCT SERIES 32 through 35

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. *Beam size must be specified.* Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

FOR PRODUCT SERIES 36

Work-rated trolleys are available for Standard I Beam or WF beam, 4- $\frac{5}{8}$ inch to 8 inch flange width. Beam size must be specified. These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches are available on application.

NOTE: The first two digits of the product number designates the hoist product series (3330710) is a product series 33).

8. SPECIFY OTHER MODIFICATIONS AND ACCESSORIES: See Section 35 for further specification.

SPECIAL APPLICATION HOISTS: Many other lifting speeds and lifting distances that are not found in following pages are available on application. They require special application consideration. Contact your nearest WRIGHT representative.

1 TON

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 5/16"

30-4

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	45	45-15	45
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3
27 H3	Lug		3243950	3244000	3244050
	Plain Trolley		3243960	3244010	3244060
	Geared Trolley		3243970	3244020	3244070
	Mtz Trolley - 65 FPM SS		3243980	3244030	3244080
	Mtz Trolley - 125 FPM VS		3243990	3244040	3244090
	A		7-3/8	7-3/8	7-3/8
	B		27-3/8	25-3/8	28-1/2
	C		27-5/8	27-5/8	27-5/8
	H ₁		2-3/4	2-3/4	2-3/4
	H ₂		2-1/4	2-1/4	2-1/4
38 H3	Lug		3244100	3244150	3244200
	Plain Trolley		3244110	3244160	3244210
	Geared Trolley		3244120	3244170	3244220
	Mtz Trolley - 65 FPM SS		3244130	3244180	3244230
	Mtz Trolley - 125 FPM VS		3244140	3244190	3244240
	A		7-3/8	7-3/8	7-3/8
	B		29-3/8	27-3/8	30-1/2
	C		29-5/8	29-5/8	29-5/8
	H ₁		4-3/4	4-3/4	4-3/4
	H ₂		2-1/4	2-1/4	2-1/4
52 H3	Lug		3244250	3244300	3244350
	Plain Trolley		3244260	3244310	3244360
	Geared Trolley		3244270	3244320	3244370
	Mtz Trolley - 65 FPM SS		3244280	3244330	3244380
	Mtz Trolley - 125 FPM VS		3244290	3244340	3244390
	A		7-5/8	7-5/8	7-5/8
	B		31-7/8	29-7/8	33
	C		32-1/8	32-1/8	32-1/8
	H ₁		7-1/4	7-1/4	7-1/4
	H ₂		2-1/4	2-1/4	2-1/4
66 H3	Lug		3244400	3244450	3244500
	Plain Trolley		3244410	3244460	3244510
	Geared Trolley		3244420	3244470	3244520
	Mtz Trolley - 65 FPM SS		3244430	3244480	3244530
	Mtz Trolley - 125 FPM VS		3244440	3244490	3244540
	A		7-5/8	7-5/8	7-5/8
	B		34-3/8	32-3/8	35-1/2
	C		34-5/8	34-5/8	34-5/8
	H ₁		9-3/4	9-3/4	9-3/4
	H ₂		2-1/4	2-1/4	2-1/4
80 H3	Lug		3244550	3244600	3244650
	Plain Trolley		3244560	3244610	3244660
	Geared Trolley		3244570	3244620	3244670
	Mtz Trolley - 65 FPM SS		3244580	3244630	3244680
	Mtz Trolley - 125 FPM VS		3244590	3244640	3244690
	A		7-5/8	7-5/8	7-5/8
	B		36-7/8	34-7/8	38
	C		37-1/8	37-1/8	37-1/8
	H ₁		12-1/4	12-1/4	12-1/4
	H ₂		2-1/4	2-1/4	2-1/4
110 H3	Lug		3244700	3244750	3244800
	Plain Trolley	33	3244710	3244760	3244810
	Geared Trolley		3244720	3244770	3244820
	Mtz Trolley - 65 FPM SS		3244730	3244780	3244830
	Mtz Trolley - 125 FPM VS		3244740	3244790	3244840
	A		7-5/8	7-5/8	7-5/8
	B		42-3/8	40-3/8	43-1/2
	C		42-5/8	42-5/8	42-5/8
	H ₁		17-3/4	17-3/4	17-3/4
	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		17-7/8	17-7/8	17-7/8
	T ₂		35-3/4	35-3/4	35-3/4

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-5 Issued 2-19-88


STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 5/16"

1
TON


52, 66, 80, 110 FOOT LIFTS

Wheel Dia. 5




Straight track trolley

27, 38 FOOT LIFTS




Curve track trolley - 72" Min. Radius

ALL LIFTS




MOTORIZED TROLLEY


Wheel Dia. 5






Straight track trolley



Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

		Lifting Speed	PRODUCT NUMBERS AND CLEARANCES		
Lift in Feet	Hoist Suspension	Hoist Control	30	30-10	30
			Single Speed	Two Speed	Variable Speed
		HP	2	2-2/3	2
H4	27	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂	3220000 3220010 3220020 3220030 3220040 7-3/8 25-3/8 27-5/8 2-3/4 2-1/4	3220050 3220060 3220070 3220080 3220090 7-3/8 25-3/8 27-5/8 2-3/4 2-1/4	3220100 3220110 3220120 3220130 3220140 7-3/8 25-3/8 27-5/8 2-3/4 2-1/4
	38	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂	3220150 3220160 3220170 3220180 3220190 7-3/8 27-3/8 29-5/8 4-3/4 2-1/4	3220200 3220210 3220220 3220230 3220240 7-3/8 27-3/8 29-5/8 4-3/4 2-1/4	3220250 3220260 3220270 3220280 3220290 7-3/8 27-3/8 29-5/8 4-3/4 2-1/4
	52	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3220300 3220310 3220320 3220330 3220340 7-5/8 29-7/8 32-1/8 7-1/4 2-1/4 7-3/8 14-3/4	3220350 3220360 3220370 3220380 3220390 7-5/8 29-7/8 32-1/8 7-1/4 2-1/4 7-3/8 14-3/4	3220400 3220410 3220420 3220430 3220440 7-5/8 29-7/8 32-1/8 7-1/4 2-1/4 7-3/8 14-3/4
	66	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3220450 3220460 3220470 3220480 3220490 7-5/8 32-3/8 34-5/8 9-3/4 2-1/4 9-7/8 19-3/4	3220500 3220510 3220520 3220530 3220540 7-5/8 32-3/8 34-5/8 9-3/4 2-1/4 9-7/8 19-3/4	3220550 3220560 3220570 3220580 3220590 7-5/8 32-3/8 34-5/8 9-3/4 2-1/4 9-7/8 19-3/4
	80	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3220600 3220610 3220620 3220630 3220640 7-5/8 34-7/8 37-1/8 12-1/4 2-1/4 12-3/8 24-3/4	3220650 3220660 3220670 3220680 3220690 7-5/8 34-7/8 37-1/8 12-1/4 2-1/4 12-3/8 24-3/4	3220700 3220710 3220720 3220730 3220740 7-5/8 34-7/8 37-1/8 12-1/4 2-1/4 12-3/8 24-3/4
	110	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3220750 3220760 3220770 3220780 3220790 7-5/8 40-3/8 42-5/8 17-3/4 2-1/4 17-7/8 35-3/4	3220800 3220810 3220820 3220830 3220840 7-5/8 40-3/8 42-5/8 17-3/4 2-1/4 17-7/8 35-3/4	3220850 3220860 3220870 3220880 3220890 7-5/8 40-3/8 42-5/8 17-3/4 2-1/4 17-7/8 35-3/4

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-7 Issued 2-19-88


STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 5/16"

1
TON


52, 66, 80, 110 FOOT LIFTS

Wheel Dia. 5




Straight track trolley

27, 38 FOOT LIFTS




Curve track trolley - 72" Min. Radius

ALL LIFTS




MOTORIZED TROLLEY


Wheel Dia. 5





Straight track trolley




Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING



WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer.

Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

1 TON

CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 1/4"

30-8

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30	45	45-15	45
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	2	2-2/3	2	3	3-1	3
H3	23	Lug				3244850	3244900	3244950
		Plain Trolley				3244860	3244910	3244960
		Geared Trolley				3244870	3244920	3244970
		Mtz Trolley - 65 FPM SS				3244880	3244930	3244980
		Mtz Trolley - 125 FPM VS				3244890	3244940	3244990
		B				31-7/8	29-7/8	33
H4	23	C				32-1/8	32-1/8	32-1/8
		Lug	3232300	3232350	3232400			
		Plain Trolley	3232310	3232360	3232410			
		Geared Trolley	3232320	3232370	3232420			
		Mtz Trolley - 65 FPM SS	3232330	3232380	3232430			
		Mtz Trolley - 125 FPM VS	3232340	3232390	3232440			
H3	31	B	29-7/8	29-7/8	29-7/8			
		C	32-1/8	32-1/8	32-1/8			
		Lug				3245000	3245050	3245100
		Plain Trolley				3245010	3245060	3245110
		Geared Trolley				3245020	3245070	3245120
		Mtz Trolley - 65 FPM SS				3245030	3245080	3245130
H4	31	Mtz Trolley - 125 FPM VS				3245040	3245090	3245140
		B				34-3/8	32-3/8	35-1/2
		C				34-5/8	34-5/8	34-5/8
		Lug	3232450	3232500	3232550			
		Plain Trolley	3232460	3232510	3232560			
		Geared Trolley	3232470	3232520	3232570			
H3	39	Mtz Trolley - 65 FPM SS	3232480	3232530	3232580			
		Mtz Trolley - 125 FPM VS	3232490	3232540	3232590			
		B	32-3/8	32-3/8	32-3/8			
		C	34-5/8	34-5/8	34-5/8			
		Lug				3245150	3245200	3245250
		Plain Trolley				3245160	3245210	3245260
H4	39	Geared Trolley				3245170	3245220	3245270
		Mtz Trolley - 65 FPM SS				3245180	3245230	3245280
		Mtz Trolley - 125 FPM VS				3245190	3245240	3245290
		B				36-7/8	34-7/8	38
		C				37-1/8	37-1/8	37-1/8
		Lug	3232600	3232650	3232700			
H3	58	Plain Trolley	3232610	3232660	3232710			
		Geared Trolley	3232620	3232670	3232720			
		Mtz Trolley - 65 FPM SS	3232630	3232680	3232730			
		Mtz Trolley - 125 FPM VS	3232640	3232690	3232740			
		B	34-7/8	34-7/8	34-7/8			
		C	37-1/8	37-1/8	37-1/8			
H4	58	Lug				3245300	3245350	3245400
		Plain Trolley				3245310	3245360	3245410
		Geared Trolley				3245320	3245370	3245420
		Mtz Trolley - 65 FPM SS				3245330	3245380	3245430
		Mtz Trolley - 125 FPM VS				3245340	3245390	3245440
		B				42-3/8	40-3/8	43-1/2
H3	58	C				42-5/8	42-5/8	42-5/8
		Lug	3232750	3232800	3232850			
		Plain Trolley	3232760	3232810	3232860			
		Geared Trolley	3232770	3232820	3232870			
		Mtz Trolley - 65 FPM SS	3232780	3232830	3232880			
		Mtz Trolley - 125 FPM VS	3232790	3232840	3232890			
H4	58	B	40-3/8	40-3/8	40-3/8			
		C	42-5/8	42-5/8	42-5/8			

(a) Optional trolley brake.

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



**WRIGHT Work-rated
ELECTRIC HOISTS**


30-9 Issued 2-19-88

**CLOSE HEADROOM
CROSS MOUNTED**
2 PART DOUBLE REEVING - 1/4"


**1
TON**

Wheel Dia. 5

ALL LIFTS




Straight track trolley




MOTORIZED TROLLEY



Wheel Dia. 5



Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING



CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 1/4"

30-10

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	45	45-15	45
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3
23 H3	Lug		3247020	3247070	3247120
	Plain Trolley		3247030	3247080	3247130
	Geared Trolley		3247040	3247090	3247140
	Mtz Trolley - 65 FPM SS		3247050	3247100	3247150
	Mtz Trolley - 125 FPM VS		3247060	3247110	3247160
	B		29-7/8	29-7/8	29-7/8
	C		32-1/8	32-1/8	32-1/8
	T ₁		7-3/8	7-3/8	7-3/8
31 H3	Lug		3247170	3247220	3247270
	Plain Trolley		3247180	3247230	3247280
	Geared Trolley		3247190	3247240	3247290
	Mtz Trolley - 65 FPM SS		3247200	3247250	3247300
	Mtz Trolley - 125 FPM VS		3247210	3247260	3247310
	B		32-3/8	32-3/8	32-3/8
	C		34-5/8	34-5/8	34-5/8
	T ₁		9-7/8	9-7/8	9-7/8
39 H3	Lug		3247320	3247370	3247420
	Plain Trolley		3247330	3247380	3247430
	Geared Trolley		3247340	3247390	3247440
	Mtz Trolley - 65 FPM SS		3247350	3247400	3247450
	Mtz Trolley - 125 FPM VS		3247360	3247410	3247460
	B		34-7/8	34-7/8	34-7/8
	C		37-1/8	37-1/8	37-1/8
	T ₁		12-3/8	12-3/8	12-3/8
58 H3	Lug		3247470	3247520	3247570
	Plain Trolley		3247480	3247530	3247580
	Geared Trolley		3247490	3247540	3247590
	Mtz Trolley - 65 FPM SS		3247500	3247550	3247600
	Mtz Trolley - 125 FPM VS		3247510	3247560	3247610
	B		40-3/8	40-3/8	40-3/8
	C		42-5/8	42-5/8	42-5/8
	T ₁		17-7/8	17-7/8	17-7/8
	T ₂		35-3/4	35-3/4	35-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:



Speed	65 FPM	125 FPM
Control	Single Speed	5 Step. Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.



Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

1 TON

CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 1/4"

30-12

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed			
		Hoist Control	30	30-10	30
		HP	Single Speed	Two Speed	Variable Speed
			2	2-2/3	2
H4 23	Lug		3246420	3246470	3246520
	Plain Trolley		3246430	3246480	3246530
	Geared Trolley		3246440	3246490	3246540
	Mtz Trolley - 65 FPM SS		3246450	3246500	3246550
	Mtz Trolley - 125 FPM VS		3246460	3246510	3246560
	B		29-7/8	29-7/8	29-7/8
	C		32-1/8	32-1/8	32-1/8
	T ₁		7-3/8	7-3/8	7-3/8
	T ₂		14-3/4	14-3/4	14-3/4
H4 31	Lug		3246570	3246620	3246670
	Plain Trolley		3246580	3246630	3246680
	Geared Trolley		3246590	3246640	3246690
	Mtz Trolley - 65 FPM SS		3246600	3246650	3246700
	Mtz Trolley - 125 FPM VS		3246610	3246660	3246710
	B		32-3/8	32-3/8	32-3/8
	C		34-5/8	34-5/8	34-5/8
	T ₁		9-7/8	9-7/8	9-7/8
	T ₂		19-3/4	19-3/4	19-3/4
H4 39	Lug		3246720	3246770	3246820
	Plain Trolley		3246730	3246780	3246830
	Geared Trolley		3246740	3246790	3246840
	Mtz Trolley - 65 FPM SS		3246750	3246800	3246850
	Mtz Trolley - 125 FPM VS		3246760	3246810	3246860
	B		34-7/8	34-7/8	34-7/8
	C		37-1/8	37-1/8	37-1/8
	T ₁		12-3/8	12-3/8	12-3/8
	T ₂		24-3/4	24-3/4	24-3/4
H4 58	Lug		3246870	3246920	3246970
	Plain Trolley		3246880	3246930	3246980
	Geared Trolley		3246890	3246940	3246990
	Mtz Trolley - 65 FPM SS		3246900	3246950	3247000
	Mtz Trolley - 125 FPM VS		3246910	3246960	3247010
	B		40-3/8	40-3/8	40-3/8
	C		42-5/8	42-5/8	42-5/8
	T ₁		17-7/8	17-7/8	17-7/8
	T ₂		35-3/4	35-3/4	35-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



WRIGHT Work-rated ELECTRIC HOISTS

30-13 Issued 2-19-88



CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 1/4"

1
TON



ALL LIFTS

Wheel Dia. 5





MOTORIZED TROLLEY

Wheel Dia. 5



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

1 1/2 TON

STANDARD HEADROOM PARALLEL MOUNTED

30-14

2 PART SINGLE REEVING - 5/16"

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30	40	40-13	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
H3	Lug		3222400	3222450	3222500	3223300	3223350	3223400
	Plain Trolley		3222410	3222460	3222510	3223310	3223360	3223410
	Geared Trolley		3222420	3222470	3222520	3223320	3223370	3223420
	Mtz Trolley - 65 FPM SS		3222430	3222480	3222530	3223330	3223380	3223430
	Mtz Trolley - 125 FPM VS		3222440	3222490	3222540	3223340	3223390	3223440
	A		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	B		25-3/8	25-3/8	25-3/8	25-3/8	27-3/8	25-3/8
	C		27-5/8	27-5/8	27-5/8	27-5/8	27-5/8	27-5/8
	H ₁		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	Lug		3222550	3222600	3222650	3223450	3223500	3223550
	Plain Trolley		3222560	3222610	3222660	3223460	3223510	3223560
	Geared Trolley		3222570	3222620	3222670	3223470	3223520	3223570
	Mtz Trolley - 65 FPM SS		3222580	3222630	3222680	3223480	3223530	3223580
	Mtz Trolley - 125 FPM VS		3222590	3222640	3222690	3223490	3223540	3223590
	A		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	B		27-3/8	27-3/8	27-3/8	27-3/8	29-3/8	27-3/8
	C		29-5/8	29-5/8	29-5/8	29-5/8	29-5/8	29-5/8
	H ₁		4-3/4	4-3/4	4-3/4	4-3/4	4-3/4	4-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	Lug		3222700	3222750	3222800	3223600	3223650	3223700
	Plain Trolley		3222710	3222760	3222810	3223610	3223660	3223710
	Geared Trolley		3222720	3222770	3222820	3223620	3223670	3223720
	Mtz Trolley - 65 FPM SS		3222730	3222780	3222830	3223630	3223680	3223730
	Mtz Trolley - 125 FPM VS		3222740	3222790	3222840	3223640	3223690	3223740
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
	C		32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
	H ₁		7-1/4	7-1/4	7-1/4	7-1/4	7-1/4	7-1/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	T ₁		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	T ₂		14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4
H3	Lug		3222850	3222900	3222950	3223750	3223800	3223850
	Plain Trolley		3222860	3222910	3222960	3223760	3223810	3223860
	Geared Trolley		3222870	3222920	3222970	3223770	3223820	3223870
	Mtz Trolley - 65 FPM SS		3222880	3222930	3222980	3223780	3223830	3223880
	Mtz Trolley - 125 FPM VS		3222890	3222940	3222990	3223790	3223840	3223890
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		32-3/8	32-3/8	32-3/8	32-3/8	34-3/8	32-3/8
	C		34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
	H ₁		9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	T ₁		9-7/8	9-7/8	9-7/8	9-7/8	9-7/8	9-7/8
	T ₂		19-3/4	19-3/4	19-3/4	19-3/4	19-3/4	19-3/4
H3	Lug		3223000	3223050	3223100	3223900	3223950	3224000
	Plain Trolley		3223010	3223060	3223110	3223910	3223960	3224010
	Geared Trolley		3223020	3223070	3223120	3223920	3223970	3224020
	Mtz Trolley - 65 FPM SS		3223030	3223080	3223130	3223930	3223980	3224030
	Mtz Trolley - 125 FPM VS		3223040	3223090	3223140	3223940	3223990	3224040
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
	C		37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
	H ₁		12-1/4	12-1/4	12-1/4	12-1/4	12-1/4	12-1/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	T ₁		12-3/8	12-3/8	12-3/8	12-3/8	12-3/8	12-3/8
	T ₂		24-3/4	24-3/4	24-3/4	24-3/4	24-3/4	24-3/4
H3	Lug		3223150	3223200	3223250	3224050	3224100	3224150
	Plain Trolley		3223160	3223210	3223260	3224060	3224110	3224160
	Geared Trolley		3223170	3223220	3223270	3224070	3224120	3224170
	Mtz Trolley - 65 FPM SS		3223180	3223230	3223280	3224080	3224130	3224180
	Mtz Trolley - 125 FPM VS		3223190	3223240	3223290	3224090	3224140	3224190
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
	C		42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8
	H ₁		17-3/4	17-3/4	17-3/4	17-3/4	17-3/4	17-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
H3	T ₁		17-7/8	17-7/8	17-7/8	17-7/8	17-7/8	17-7/8
	T ₂		35-3/4	35-3/4	35-3/4	35-3/4	35-3/4	35-3/4

All dimensions in inches.



WRIGHT Work-rated
ELECTRIC HOISTS
30-15 Issued 2-19-88


STANDARD HEADROOM
PARALLEL MOUNTED
2 PART SINGLE REEVING - 5/16"

1 1/2
TON


52,66,80,110 FOOT LIFTS

27,38 FOOT LIFTS


ALL LIFTS




Straight track trolley




Curve track trolley 72" Min. Radius




MOTORIZED TROLLEY






Straight track trolley



Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30			40		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
H3	Lug		3233900	3233950	3234000	3234500	3234550	3234600
	Plain Trolley		3233910	3233960	3234010	3234510	3234560	3234610
	Geared Trolley		3233920	3233970	3234020	3234520	3234570	3234620
	Mtz Trolley - 65 FPM		3233930	3233980	3234030	3234530	3234580	3234630
	Mtz Trolley - 125 FPM		3233940	3233990	3234040	3234540	3234590	3234640
		B	29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
		C	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
H3	Lug		3234050	3234100	3234150	3234650	3234700	3234750
	Plain Trolley		3234060	3234110	3234160	3234660	3234710	3234760
	Geared Trolley		3234070	3234120	3234170	3234670	3234720	3234770
	Mtz Trolley - 65 FPM		3234080	3234130	3234180	3234680	3234730	3234780
	Mtz Trolley - 125 FPM		3234090	3234140	3234190	3234690	3234740	3234790
		B	32-3/8	32-3/8	32-3/8	32-3/8	34-3/8	32-3/8
		C	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
H3	Lug		3234200	3234250	3234300	3234800	3234850	3234900
	Plain Trolley		3234210	3234260	3234310	3234810	3234860	3234910
	Geared Trolley		3234220	3234270	3234320	3234820	3234870	3234920
	Mtz Trolley - 65 FPM		3234230	3234280	3234330	3234830	3234880	3234930
	Mtz Trolley - 125 FPM		3234240	3234290	3234340	3234840	3234890	3234940
		B	34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
		C	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
H3	Lug		3234350	3234400	3234450	3234950	3235000	3235050
	Plain Trolley		3234360	3234410	3234460	3234960	3235010	3235060
	Geared Trolley		3234370	3234420	3234470	3234970	3235020	3235070
	Mtz Trolley - 65 FPM		3234380	3234430	3234480	3234980	3235030	3235080
	Mtz Trolley - 125 FPM		3234390	3234440	3234490	3234990	3235040	3235090
		B	40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
		C	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**



30-17 Issued 2-19-88

**CLOSE HEADROOM
CROSS MOUNTED**



2 PART DOUBLE REEVING - 1/4"

**1 1/2
TON**



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

2 TON

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 3/8"

30-18

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22			30		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
21	Lug		3225100	3225150	3225200	3226000	3226050	3226100
	Plain Trolley		3225110	3225160	3225210	3226010	3226060	3226110
	Geared Trolley		3225120	3225170	3225220	3226020	3226070	3226120
	Mtz Trolley - 65 FPM SS		3225130	3225180	3225230	3226030	3226080	3226130
	Mtz Trolley - 125 FPM VS		3225140	3225190	3225240	3226040	3226090	3226140
	A		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	B		25-3/8	25-3/8	25-3/8	25-3/8	27-3/8	25-3/8
	C		27-5/8	27-5/8	27-5/8	27-5/8	27-5/8	27-5/8
	H ₁		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
30	Lug		3225250	3225300	3225350	3226150	3226200	3226250
	Plain Trolley		3225260	3225310	3225360	3226160	3226210	3226260
	Geared Trolley		3225270	3225320	3225370	3226170	3226220	3226270
	Mtz Trolley - 65 FPM SS		3225280	3225330	3225380	3226180	3226230	3226280
	Mtz Trolley - 125 FPM VS		3225290	3225340	3225390	3226190	3226240	3226290
	A		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	B		27-3/8	27-3/8	27-3/8	27-3/8	29-3/8	27-3/8
	C		29-5/8	29-5/8	29-5/8	29-5/8	29-5/8	29-5/8
	H ₁		4-3/4	4-3/4	4-3/4	4-3/4	4-3/4	4-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
41	Lug		3225400	3225450	3225500	3226300	3226350	3226400
	Plain Trolley		3225410	3225460	3225510	3226310	3226360	3226410
	Geared Trolley		3225420	3225470	3225520	3226320	3226370	3226420
	Mtz Trolley - 65 FPM SS		3225430	3225480	3225530	3226330	3226380	3226430
	Mtz Trolley - 125 FPM VS		3225440	3225490	3225540	3226340	3226390	3226440
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
	C		32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
	H ₁		7-1/4	7-1/4	7-1/4	7-1/4	7-1/4	7-1/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
52	Lug		3225550	3225600	3225650	3226450	3226500	3226550
	Plain Trolley		3225560	3225610	3225660	3226460	3226510	3226560
	Geared Trolley		3225570	3225620	3225670	3226470	3226520	3226570
	Mtz Trolley - 65 FPM SS		3225580	3225630	3225680	3226480	3226530	3226580
	Mtz Trolley - 125 FPM VS		3225590	3225640	3225690	3226490	3226540	3226590
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		32-3/8	32-3/8	32-3/8	32-3/8	32-3/8	32-3/8
	C		34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
	H ₁		9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
63	Lug		3225700	3225750	3225800	3226600	3226650	3226700
	Plain Trolley		3225710	3225760	3225810	3226610	3226660	3226710
	Geared Trolley		3225720	3225770	3225820	3226620	3226670	3226720
	Mtz Trolley - 65 FPM SS		3225730	3225780	3225830	3226630	3226680	3226730
	Mtz Trolley - 125 FPM VS		3225740	3225790	3225840	3226640	3226690	3226740
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
	C		37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
	H ₁		12-1/4	12-1/4	12-1/4	12-1/4	12-1/4	12-1/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
88	Lug		3225850	3225900	3225950	3226750	3226800	3226850
	Plain Trolley	33	3225860	3225910	3225960	3226760	3226810	3226860
	Geared Trolley		3225870	3225920	3225970	3226770	3226820	3226870
	Mtz Trolley - 65 FPM SS		3225880	3225930	3225980	3226780	3226830	3226880
	Mtz Trolley - 125 FPM VS		3225890	3225940	3225990	3226790	3226840	3226890
	A		7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B		40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
	C		42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8
	H ₁		17-3/4	17-3/4	17-3/4	17-3/4	17-3/4	17-3/4
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-19 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 3/8"




2
TON

41, 52, 63, 88 FOOT LIFTS

21, 30 FOOT LIFTS




ALL LIFTS

Wheel Dia. 5






MOTORIZED TROLLEY

Wheel Dia. 5



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 3/8"

30-20

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	45	45-15	45
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	6-1/4	6-1/4-2	6-1/4
H3	Lug		3330000	3330050	3330100
	Plain Trolley		3330010	3330060	3330110
	Geared Trolley		3330020	3330070	3330120
	Mtz Trolley - 65 FPM SS		3330030	3330080	3330130
	Mtz Trolley - 125 FPM VS		3330040	3330090	3330140
	B		24-3/8	27-3/4	26-1/2
	C		28-1/8	28-1/8	28-1/8
	H ₁		2-1/2	2-1/2	2-1/2
H3	H ₂		1-1/2	1-1/2	1-1/2
	Lug		3330150	3330200	3330250
	Plain Trolley		3330160	3330210	3330260
	Geared Trolley		3330170	3330220	3330270
	Mtz Trolley - 65 FPM SS		3330180	3330230	3330280
	Mtz Trolley - 125 FPM VS		3330190	3330240	3330290
	B		26-5/8	30	28-3/4
	C		30-3/8	30-3/8	30-3/8
H3	H ₁		4-1/8	4-1/8	4-1/8
	H ₂		2-1/4	2-1/4	2-1/4
	Lug		3330300	3330350	3330400
	Plain Trolley		3330310	3330360	3330410
	Geared Trolley		3330320	3330370	3330420
	Mtz Trolley - 65 FPM SS		3330330	3330380	3330430
	Mtz Trolley - 125 FPM VS		3330340	3330390	3330440
	B		30-3/8	33-3/4	32-1/2
H3	C		34-1/8	34-1/8	34-1/8
	H ₁		7-7/8	7-7/8	7-7/8
	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		8	8	8
	T ₂		7-3/4	7-3/4	7-3/4
H3	Lug		3330450	3330500	3330550
	Plain Trolley		3330460	3330510	3330560
	Geared Trolley		3330470	3330520	3330570
	Mtz Trolley - 65 FPM SS		3330480	3330530	3330580
	Mtz Trolley - 125 FPM VS		3330490	3330540	3330590
	B		33-7/8	37-1/4	36
	C		37-5/8	37-5/8	37-5/8
	H ₁		11-3/8	11-3/8	11-3/8
H3	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		11-1/2	11-1/2	11-1/2
	T ₂		11-1/4	11-1/4	11-1/4
H3	Lug		3348200	3348250	3348300
	Plain Trolley		3348210	3348260	3348310
	Geared Trolley		3348220	3348270	3348320
	Mtz Trolley - 65 FPM SS		3348230	3348280	3348330
	Mtz Trolley - 125 FPM VS		3348240	3348290	3348340
	B		36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8
	H ₁		14-3/8	14-3/8	14-3/8
H3	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		14-1/2	14-1/2	14-1/2
	T ₂		14-1/4	14-1/4	14-1/4
H3	Lug		3330600	3330650	3330700
	Plain Trolley	33	3330610	3330660	3330710
	Geared Trolley		3330620	3330670	3330720
	Mtz Trolley - 65 FPM SS		3330630	3330680	3330730
	Mtz Trolley - 125 FPM VS		3330640	3330690	3330740
	B		41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8
	H ₁		18-7/8	18-7/8	18-7/8
H3	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		19	19	19
	T ₂		18-3/4	18-3/4	18-3/4

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-21 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 3/8"


2 TON

54, 74, 90, 115 FOOT LIFTS


22, 34 FOOT LIFTS

ALL LIFTS


Wheel Dia. 5



Straight track trolley




Curve track trolley - 72" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 5






Straight track trolley



Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

**2
TON****STANDARD HEADROOM
PARALLEL MOUNTED****2 PART SINGLE REEVING - 3/8"**

30-22

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30		
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	4	4-1-1/3	4
H4	Lug		3348350	3348400	3348450
	Plain Trolley		3348360	3348410	3348460
	Geared Trolley		3348370	3348420	3348470
	Mtz Trolley - 65 FPM SS		3348380	3348430	3348480
	Mtz Trolley - 125 FPM VS		3348390	3348440	3348490
	B		24-3/8	25-1/2	24-3/8
	C		28-1/8	28-1/8	28-1/8
	H ₁		2-1/2	2-1/2	2-1/2
H4	H ₂		1-1/2	1-1/2	1-1/2
	Lug		3348500	3348550	3348600
	Plain Trolley		3348510	3348560	3348610
	Geared Trolley		3348520	3348570	3348620
	Mtz Trolley - 65 FPM SS		3348530	3348580	3348630
	Mtz Trolley - 125 FPM VS		3348540	3348590	3348640
	B		26-5/8	27-3/4	26-5/8
	C		30-3/8	30-3/8	30-3/8
H4	H ₁		4-1/8	4-1/8	4-1/8
	H ₂		2-1/4	2-1/4	2-1/4
	Lug		3348650	3348700	3348750
	Plain Trolley		3348660	3348710	3348760
	Geared Trolley		3348670	3348720	3348770
	Mtz Trolley - 65 FPM SS		3348680	3348730	3348780
	Mtz Trolley - 125 FPM VS		3348690	3348740	3348790
	B		30-3/8	31-1/2	30-3/8
H4	C		34-1/8	34-1/8	34-1/8
	H ₁		7-7/8	7-7/8	7-7/8
	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		8	8	8
	T ₂		7-3/4	7-3/4	7-3/4
H4	Lug		3348800	3348850	3348900
	Plain Trolley		3348810	3348860	3348910
	Geared Trolley		3348820	3348870	3348920
	Mtz Trolley - 65 FPM SS		3348830	3348880	3348930
	Mtz Trolley - 125 FPM VS		3348840	3348890	3348940
	B		33-7/8	35	33-7/8
	C		37-5/8	37-5/8	37-5/8
	H ₁		11-3/8	11-3/8	11-3/8
H4	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		11-1/2	11-1/2	11-1/2
	T ₂		11-1/4	11-1/4	11-1/4
H4	Lug		3348950	3349000	3349050
	Plain Trolley		3348960	3349010	3349060
	Geared Trolley		3348970	3349020	3349070
	Mtz Trolley - 65 FPM SS		3348980	3349030	3349080
	Mtz Trolley - 125 FPM VS		3348990	3349040	3349090
	B		36-7/8	38	36-7/8
	C		40-5/8	40-5/8	40-5/8
	H ₁		14-3/8	14-3/8	14-3/8
H4	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		14-1/2	14-1/2	14-1/2
	T ₂		14-1/4	14-1/4	14-1/4
H4	Lug		3349100	3349150	3349200
	Plain Trolley		3349110	3349160	3349210
	Geared Trolley		3349120	3349170	3349220
	Mtz Trolley - 65 FPM SS		3349130	3349180	3349230
	Mtz Trolley - 125 FPM VS		3349140	3349190	3349240
	B		41-3/8	42-1/2	41-3/8
	C		45-1/8	45-1/8	45-1/8
	H ₁		18-7/8	18-7/8	18-7/8
H4	H ₂		2-1/4	2-1/4	2-1/4
	T ₁		19	19	19
	T ₂		18-3/4	18-3/4	18-3/4

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-23 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 3/8"


2
TON

54, 74, 90, 115 FOOT LIFTS



22, 34 FOOT LIFTS

ALL LIFTS

Wheel Dia. 5




Curve track trolley - 72" Min. Radius





MOTORIZED TROLLEY




Wheel Dia. 5



Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22			30		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
23 H3	Lug		3235700	3235750	3235800	3236300	3236350	3236400
	Plain Trolley		3235710	3235760	3235810	3236310	3236360	3236410
	Geared Trolley		3235720	3235770	3235820	3236320	3236370	3236420
	Mtz Trolley - 65 FPM		3235730	3235780	3235830	3236330	3236380	3236430
	Mtz Trolley - 125 FPM		3235740	3235790	3235840	3236340	3236390	3236440
		B	29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
		C	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
31 H3	Lug		3235850	3235900	3235950	3236450	3236500	3236550
	Plain Trolley		3235860	3235910	3235960	3236460	3236510	3236560
	Geared Trolley		3235870	3235920	3235970	3236470	3236520	3236570
	Mtz Trolley - 65 FPM		3235880	3235930	3235980	3236480	3236530	3236580
	Mtz Trolley - 125 FPM		3235890	3235940	3235990	3236490	3236540	3236590
		B	32-3/8	32-3/8	32-3/8	32-3/8	34-3/8	32-3/8
		C	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
39 H3	Lug		3236000	3236050	3236100	3236600	3236650	3236700
	Plain Trolley		3236010	3236060	3236110	3236610	3236660	3236710
	Geared Trolley		3236020	3236070	3236120	3236620	3236670	3236720
	Mtz Trolley - 65 FPM		3236030	3236080	3236130	3236630	3236680	3236730
	Mtz Trolley - 125 FPM		3236040	3236090	3236140	3236640	3236690	3236740
		B	34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
		C	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
58 H3	Lug		3236150	3236200	3236250	3236750	3236800	3236850
	Plain Trolley		3236160	3236210	3236260	3236760	3236810	3236860
	Geared Trolley		3236170	3236220	3236270	3236770	3236820	3236870
	Mtz Trolley - 65 FPM		3236180	3236230	3236280	3236780	3236830	3236880
	Mtz Trolley - 125 FPM		3236190	3236240	3236290	3236790	3236840	3236890
		B	40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
		C	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**


30-25 Issued 2-19-88

**CLOSE HEADROOM
CROSS MOUNTED**


2 PART DOUBLE REEVING - 1/4"

**2
TON**


ALL LIFTS




Straight track trolley




MOTORIZED TROLLEY




Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING



WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

**2
TON****CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 1/4"

30-26

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control	30	30-10	30	45	45-15	45
		HP	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			4	4-1-1/3	4	6-1/4	6-1/4-2	6-1/4
H3	31	Lug				3336650	3336700	3336750
		Plain Trolley				3336660	3336710	3336760
		Geared Trolley				3336670	3336720	3336770
		Mtz Trolley - 65 FPM SS				3336680	3336730	3336780
		Mtz Trolley - 125 FPM VS				3336690	3336740	3336790
		B				30-3/8	33-3/4	32-1/2
H4	31	C				34-1/8	34-1/8	34-1/8
		Lug	3349250	3349300	3349350			
		Plain Trolley	3349260	3349310	3349360			
		Geared Trolley	3349270	3339320	3349370			
		Mtz Trolley - 65 FPM SS	3349280	3349330	3349380			
		Mtz Trolley - 125 FPM VS	3349290	3349340	3349390			
H3	45	B	30-3/8	31-1/2	30-3/8			
		C	34-1/8	34-1/8	34-1/8			
		Lug				3336800	3336850	3336900
		Plain Trolley				3336810	3336860	3336910
		Geared Trolley				3336820	3336870	3336920
		Mtz Trolley - 65 FPM SS				3336830	3336880	3336930
H4	45	Mtz Trolley - 125 FPM VS				3336840	3336890	3336940
		B				33-7/8	37-1/4	36
		C				37-5/8	37-5/8	37-5/8
		Lug	3349400	3349450	3349500			
		Plain Trolley	3349410	3349460	3349510			
		Geared Trolley	3349420	3349470	3349520			
H3	57	Mtz Trolley - 65 FPM SS	3349430	3349480	3349530			
		Mtz Trolley - 125 FPM VS	3349440	3349490	3349540			
		B	33-7/8	35	33-7/8			
		C	37-5/8	37-5/8	37-5/8			
		Lug				3336950	3337000	3337050
		Plain Trolley				3336960	3337010	3337060
H4	57	Geared Trolley				3336970	3337020	3337070
		Mtz Trolley - 65 FPM SS				3336980	3337030	3337080
		Mtz Trolley - 125 FPM VS				3336990	3337040	3337090
		B				36-7/8	40-1/4	39
		C				40-5/8	40-5/8	40-5/8
		Lug	3349550	3349600	3349650			
H3	76	Plain Trolley	3349560	3349610	3349660			
		Geared Trolley	3349570	3349620	3349670			
		Mtz Trolley - 65 FPM SS	3349580	3349630	3349680			
		Mtz Trolley - 125 FPM VS	3349590	3349640	3349690			
		B	36-7/8	38	36-7/8			
		C	40-5/8	40-5/8	40-5/8			
H4	76	Lug				3337100	3337150	3337200
		Plain Trolley				3337110	3337160	3337210
		Geared Trolley				3337120	3337170	3337220
		Mtz Trolley - 65 FPM SS				3337130	3337180	3337230
		Mtz Trolley - 125 FPM VS				3337140	3337190	3337240
		B				41-3/8	44-3/4	43-1/2
H3	76	C				45-1/8	45-1/8	45-1/8
		Lug	3349700	3349750	3349800			
		Plain Trolley	3349710	3349760	3349810			
		Geared Trolley	3349720	3349770	3349820			
		Mtz Trolley - 65 FPM SS	3349730	3349780	3349830			
		Mtz Trolley - 125 FPM VS	3349740	3349790	3349840			
H4	76	B	41-3/8	42-1/2	41-3/8			
		C	45-1/8	45-1/8	45-1/8			

(a) Optional trolley brake.

All dimensions in inches.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2



WRIGHT Work-rated ELECTRIC HOISTS

30-27 Issued 2-19-88


CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 1/4"


**2
TON**

ALL LIFTS

Wheel Dia. 5




Straight track trolley




MOTORIZED TROLLEY



Wheel Dia. 5



Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 1/4"

30-28

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
H3 23	Lug		3247620	3247670	3247720	3248220	3248270	3248320
	Plain Trolley		3247630	3247680	3247730	3248230	3248280	3248330
	Geared Trolley		3247640	3247690	3247740	3248240	3248290	3248340
	Mtz Trolley - 65 FPM SS		3247650	3247700	3247750	3248250	3248300	3248350
	Mtz Trolley - 125 FPM VS		3247660	3247710	3247760	3248260	3248310	3248360
	B		29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
	C		32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
	T ₁		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	T ₂		14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4
H3 31	Lug		3247770	3247820	3247870	3248370	3248420	3248470
	Plain Trolley		3247780	3247830	3247880	3248380	3248430	3248480
	Geared Trolley		3247790	3247840	3247890	3248390	3248440	3248490
	Mtz Trolley - 65 FPM SS		3247800	3247850	3247900	3248400	3248450	3248500
	Mtz Trolley - 125 FPM VS		3247810	3247860	3247910	3248410	3248460	3248510
	B		32-3/8	32-3/8	32-3/8	32-3/8	34-3/8	32-3/8
	C		34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
	T ₁		9-7/8	9-7/8	9-7/8	9-7/8	9-7/8	9-7/8
	T ₂		19-3/4	19-3/4	19-3/4	19-3/4	19-3/4	19-3/4
H3 39	Lug		3247920	3247970	3248020	3248520	3248570	3248620
	Plain Trolley		3247930	3247980	3248030	3248530	3248580	3248630
	Geared Trolley		3247940	3247990	3248040	3248540	3248590	3248640
	Mtz Trolley - 65 FPM SS		3247950	3248000	3248050	3248550	3248600	3248650
	Mtz Trolley - 125 FPM VS		3247960	3248010	3248060	3248560	3248610	3248660
	B		34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
	C		37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
	T ₁		12-3/8	12-3/8	12-3/8	12-3/8	12-3/8	12-3/8
	T ₂		24-3/4	24-3/4	24-3/4	24-3/4	24-3/4	24-3/4
H3 58	Lug		3248070	3248120	3248170	3248670	3248720	3248770
	Plain Trolley		3248080	3248130	3248180	3248680	3248730	3248780
	Geared Trolley		3248090	3248140	3248190	3248690	3248740	3248790
	Mtz Trolley - 65 FPM SS		3248100	3248150	3248200	3248700	3248750	3248800
	Mtz Trolley - 125 FPM VS		3248110	3248160	3248210	3248710	3248760	3248810
	B		40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
	C		42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8
	T ₁		17-7/8	17-7/8	17-7/8	17-7/8	17-7/8	17-7/8
	T ₂		35-3/4	35-3/4	35-3/4	35-3/4	35-3/4	35-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2



(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

3 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 5/16"

30-30

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15			20		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	3	3-1	3	4	4-1-1/3	4
H3 19	Lug		3227950	3228000	3228050	3228850	3228900	3228950
	Plain Trolley		3227960	3228010	3228060	3228860	3228910	3228960
	Geared Trolley		3227970	3228020	3228070	3228870	3228920	3228970
	Mtz Trolley - 65 FPM SS		3227980	3228030	3228080	3228880	3228930	3228980
	Mtz Trolley - 125 FPM VS		3227990	3228040	3228090	3228890	3228940	3228990
	A	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	B	27-3/8	27-3/8	27-3/8	27-3/8	27-3/8	29-3/8	27-3/8
	C	29-5/8	29-5/8	29-5/8	29-5/8	29-5/8	29-5/8	29-5/8
	H ₁	3	3	3	3	3	3	3
	H ₂	1/2	1/2	1/2	1/2	1/2	1/2	1/2
H3 26	Lug		3228100	3228150	3228200	3229000	3229050	3229100
	Plain Trolley		3228110	3228160	3228210	3229010	3229060	3229110
	Geared Trolley		3228120	3228170	3228220	3229020	3229070	3229120
	Mtz Trolley - 65 FPM SS		3228130	3228180	3228230	3229030	3229080	3229130
	Mtz Trolley - 125 FPM VS		3228140	3228190	3228240	3229040	3229090	3229140
	A	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B	29-7/8	29-7/8	29-7/8	29-7/8	29-7/8	31-7/8	29-7/8
	C	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
	H ₁	5-5/8	5-5/8	5-5/8	5-5/8	5-5/8	5-5/8	5-5/8
	H ₂	7/8	7/8	7/8	7/8	7/8	7/8	7/8
H3 33	Lug		3228250	3228300	3228350	3229150	3229200	3229250
	Plain Trolley		3228260	3228310	3228360	3229160	3229210	3229260
	Geared Trolley		3228270	3228320	3228370	3229170	3229220	3229270
	Mtz Trolley - 65 FPM SS		3228280	3228330	3228380	3229180	3229230	3229280
	Mtz Trolley - 125 FPM VS		3228290	3228340	3228390	3229190	3229240	3229290
	A	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B	32-3/8	32-3/8	32-3/8	32-3/8	32-3/8	34-3/8	32-3/8
	C	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
	H ₁	8	8	8	8	8	8	8
	H ₂	2	2	2	2	2	2	2
H3 40	Lug		3228400	3228450	3228500	3229300	3229350	3229400
	Plain Trolley		3228410	3228460	3228510	3229310	3229360	3229410
	Geared Trolley		3228420	3228470	3228520	3229320	3229370	3229420
	Mtz Trolley - 65 FPM SS		3228430	3228480	3228530	3229330	3229380	3229430
	Mtz Trolley - 125 FPM VS		3228440	3228490	3228540	3229340	3229390	3229440
	A	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B	34-7/8	34-7/8	34-7/8	34-7/8	34-7/8	36-7/8	34-7/8
	C	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
	H ₁	10-5/8	10-5/8	10-5/8	10-5/8	10-5/8	10-5/8	10-5/8
	H ₂	3-3/8	3-3/8	3-3/8	3-3/8	3-3/8	3-3/8	3-3/8
H3 55	Lug		3228550	3228600	3228650	3229450	3229500	3229550
	Plain Trolley		3228560	3228610	3228660	3229460	3229510	3229560
	Geared Trolley		3228570	3228620	3228670	3229470	3229520	3229570
	Mtz Trolley - 65 FPM SS		3228580	3228630	3228680	3229480	3229530	3229580
	Mtz Trolley - 125 FPM VS		3228590	3228640	3228690	3229490	3229540	3229590
	A	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8	7-5/8
	B	40-3/8	40-3/8	40-3/8	40-3/8	40-3/8	42-3/8	40-3/8
	C	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8
	H ₁	16	16	16	16	16	16	16
	H ₂	6	6	6	6	6	6	6

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



WRIGHT Work-rated ELECTRIC HOISTS

30-31 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED


4 PART SINGLE REEVING - 5/16"

3
TON


26, 33, 40, 55 FOOT LIFTS

19 FOOT LIFTS


Wheel Dia. 5



Straight track trolley




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 5






Straight track trolley



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control	22	22-7	22	30	30-10	30
		HP	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
20	Lug		3330750	3330800	3330850	3330900	3330950	3331000
	Plain Trolley		3330760	3330810	3330860	3330910	3330960	3331010
	Geared Trolley		3330770	3330820	3330870	3330920	3330970	3331020
	Mtz Trolley - 65 FPM SS		3330780	3330830	3330880	3330930	3330980	3331030
	Mtz Trolley - 125 FPM VS		3330790	3330840	3330890	3330940	3330990	3331040
	B		24-3/8	25-1/2	24-3/8	24-3/8	27-3/4	26-1/2
	C		28-1/8	28-1/8	28-1/8	28-1/8	28-1/8	28-1/8
	H ₁		2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
	H ₂		1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2
32	Lug		3331050	3331100	3331150	3331200	3331250	3331300
	Plain Trolley		3331060	3331110	3331160	3331210	3331260	3331310
	Geared Trolley		3331070	3331120	3331170	3331220	3331270	3331320
	Mtz Trolley - 65 FPM SS		3331080	3331130	3331180	3331230	3331280	3331330
	Mtz Trolley - 125 FPM VS		3331090	3331140	3331190	3331240	3331290	3331340
	B		26-5/8	27-3/4	26-5/8	26-5/8	30	28-3/4
	C		30-3/8	30-3/8	30-3/8	30-3/8	30-3/8	30-3/8
	H ₁		4-1/8	4-1/8	4-1/8	4-1/8	4-1/8	4-1/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
52	Lug		3331350	3331400	3331450	3331500	3331550	3331600
	Plain Trolley		3331360	3331410	3331460	3331510	3331560	3331610
	Geared Trolley		3331370	3331420	3331470	3331520	3331570	3331620
	Mtz Trolley - 65 FPM SS		3331380	3331430	3331480	3331530	3331580	3331630
	Mtz Trolley - 125 FPM VS		3331390	3331440	3331490	3331540	3331590	3331640
	B		30-3/8	31-1/2	30-3/8	30-3/8	33-3/4	32-1/2
	C		34-1/8	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8
	H ₁		7-7/8	7-7/8	7-7/8	7-7/8	7-7/8	7-7/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		8	8	8	8	8	8
69	Lug		3349850	3349900	3349950	3350000	3350050	3350100
	Plain Trolley		3349860	3349910	3349960	3350010	3350060	3350110
	Geared Trolley		3349870	3349920	3349970	3350020	3350070	3350120
	Mtz Trolley - 65 FPM SS		3349880	3349930	3349980	3350030	3350080	3350130
	Mtz Trolley - 125 FPM VS		3349890	3349940	3349990	3350040	3350090	3350140
	B		33-7/8	35	33-7/8	33-7/8	37-1/4	36
	C		37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8
	H ₁		11-3/8	11-3/8	11-3/8	11-3/8	11-3/8	11-3/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		11-1/2	11-1/2	11-1/2	11-1/2	11-1/2	11-1/2
84	Lug		3331650	3331700	3331750	3331800	3331850	3331900
	Plain Trolley		3331660	3331710	3331760	3331810	3331860	3331910
	Geared Trolley		3331670	3331720	3331770	3331820	3331870	3331920
	Mtz Trolley - 65 FPM SS		3331680	3331730	3331780	3331830	3331880	3331930
	Mtz Trolley - 125 FPM VS		3331690	3331740	3331790	3331840	3331890	3331940
	B		36-7/8	38	36-7/8	36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8
	H ₁		14-3/8	14-3/8	14-3/8	14-3/8	14-3/8	14-3/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		14-1/2	14-1/2	14-1/2	14-1/2	14-1/2	14-1/2
108	Lug		3331950	3332000	3332050	3332100	3332150	3332200
	Plain Trolley		3331960	3332010	3332060	3332110	3332160	3332210
	Geared Trolley		3331970	3332020	3332070	3332120	3332170	3332220
	Mtz Trolley - 65 FPM SS		3331980	3332030	3332080	3332130	3332180	3332230
	Mtz Trolley - 125 FPM VS		3331990	3332040	3332090	3332140	3332190	3332240
	B		41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8
	H ₁		18-7/8	18-7/8	18-7/8	18-7/8	18-7/8	18-7/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		19	19	19	19	19	19
H3	Lug		3331950	3332000	3332050	3332100	3332150	3332200
	Plain Trolley		3331960	3332010	3332060	3332110	3332160	3332210
	Geared Trolley		3331970	3332020	3332070	3332120	3332170	3332220
	Mtz Trolley - 65 FPM SS		3331980	3332030	3332080	3332130	3332180	3332230
	Mtz Trolley - 125 FPM VS		3331990	3332040	3332090	3332140	3332190	3332240
	B		41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8
	H ₁		18-7/8	18-7/8	18-7/8	18-7/8	18-7/8	18-7/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		19	19	19	19	19	19
H3	Lug		3331950	3332000	3332050	3332100	3332150	3332200
	Plain Trolley		3331960	3332010	3332060	3332110	3332160	3332210
	Geared Trolley		3331970	3332020	3332070	3332120	3332170	3332220
	Mtz Trolley - 65 FPM SS		3331980	3332030	3332080	3332130	3332180	3332230
	Mtz Trolley - 125 FPM VS		3331990	3332040	3332090	3332140	3332190	3332240
	B		41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8
	H ₁		18-7/8	18-7/8	18-7/8	18-7/8	18-7/8	18-7/8
	H ₂		2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	T ₁		19	19	19	19	19	19

All dimensions in inches.



WRIGHT Work-rated ELECTRIC HOISTS

30-33 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 7/16"


3
TON

52, 69, 84, 108 FOOT LIFTS


20, 32 FOOT LIFTS

ALL LIFTS


Wheel Dia. 5



Straight track trolley




Curve track trolley - 72" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 5






Straight track trolley



Curve track trolley - 72" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

(a) Optional Trolley Brake

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

3 TON

CLOSE HEADROOM CROSS MOUNTED 2 PART DOUBLE REEVING - 5/16"

30-34

H3

H2

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
18	Lug		3237500	3237550	3237600	3238100	3238150	3238200
	Plain Trolley		3237510	3237560	3237610	3238110	3238160	3238210
	Geared Trolley		3237520	3237570	3237620	3238120	3238170	3238220
	Mtz Trolley - 65 FPM SS		3237530	3237580	3237630	3238130	3238180	3238230
	Mtz Trolley - 125 FPM VS		3237540	3237590	3237640	3238140	3238190	3238240
	B		29-7/8	31-7/8	29-7/8	29-7/8	35-3/8	33
	C		32-1/8	32-1/8	32-1/8	32-1/8	32-1/8	32-1/8
25	Lug		3237650	3237700	3237750	3238250	3238300	3238350
	Plain Trolley		3237660	3237710	3237760	3238260	3238310	3238360
	Geared Trolley		3237670	3237720	3237770	3238270	3238320	3238370
	Mtz Trolley - 65 FPM SS		3237680	3237730	3237780	3238280	3238330	3238380
	Mtz Trolley - 125 FPM VS		3237690	3237740	3237790	3238290	3238340	3238390
	B		32-3/8	34-3/8	32-3/8	32-3/8	37-7/8	35-1/2
	C		34-5/8	34-5/8	34-5/8	34-5/8	34-5/8	34-5/8
32	Lug		3237800	3237850	3237900	3238400	3238450	3238500
	Plain Trolley		3237810	3237860	3237910	3238410	3238460	3238510
	Geared Trolley		3237820	3237870	3237920	3238420	3238470	3238520
	Mtz Trolley - 65 FPM SS		3237830	3237880	3237930	3238430	3238480	3238530
	Mtz Trolley - 125 FPM VS		3237840	3237890	3237940	3238440	3238490	3238540
	B		34-7/8	36-7/8	34-7/8	34-7/8	40-3/8	38
	C		37-1/8	37-1/8	37-1/8	37-1/8	37-1/8	37-1/8
47	Lug		3237950	3238000	3238050	3238550	3238600	3238650
	Plain Trolley		3237960	3238010	3238060	3238560	3238610	3238660
	Geared Trolley		3237970	3238020	3238070	3238570	3238620	3238670
	Mtz Trolley - 65 FPM SS		3237980	3238030	3238080	3238580	3238630	3238680
	Mtz Trolley - 125 FPM VS		3237990	3238040	3238090	3238590	3238640	3238690
	B		40-3/8	42-3/8	40-3/8	40-3/8	45-7/8	43-1/2
	C		42-5/8	42-5/8	42-5/8	42-5/8	42-5/8	42-5/8

TOP VALUE HOISTS

(a) Optional trolley brake.

All dimensions in inches.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Variable Speed
HP	1/2	1/2

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-35 Issued 2-19-88

**CLOSE HEADROOM
CROSS MOUNTED**


2 PART DOUBLE REEVING - 5/16"

**3
TON**


ALL LIFTS

6-5/8 SS & 2S

Wheel Dia. 5




Straight track trolley




MOTORIZED TROLLEY


Wheel Dia. 5




Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING



3 TON

CLOSE HEADROOM CROSS MOUNTED 2 PART DOUBLE REEVING - 5/16"

30-36

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control	22	22-7	22	30	30-10	30
		HP	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
H3	Lug		3337250	3337300	3337350	3337400	3337450	3337500
	Plain Trolley		3337260	3337310	3337360	3337410	3337460	3337510
	Geared Trolley		3337270	3337320	3337370	3337420	3337470	3337520
	Mtz Trolley - 65 FPM SS		3337280	3337330	3337380	3337430	3337480	3337530
	Mtz Trolley - 125 FPM VS		3337290	3337340	3337390	3337440	3337490	3337540
		B	30-3/8	31-1/2	30-3/8	30-3/8	33-3/4	32-1/2
		C	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8
H3	Lug		3337550	3337600	3337650	3337700	3337750	3337800
	Plain Trolley		3337560	3337610	3337660	3337710	3337760	3337810
	Geared Trolley		3337570	3337620	3337670	3337720	3337770	3337820
	Mtz Trolley - 65 FPM SS		3337580	3337630	3337680	3337730	3337780	3337830
	Mtz Trolley - 125 FPM VS		3337590	3337640	3337690	3337740	3337790	3337840
		B	33-7/8	35	33-7/8	33-7/8	37-1/4	36
		C	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8
H3	Lug		3337850	3337900	3337950	3338000	3338050	3338100
	Plain Trolley		3337860	3337910	3337960	3338010	3338060	3338110
	Geared Trolley		3337870	3337920	3337970	3338020	3338070	3338120
	Mtz Trolley - 65 FPM SS		3337880	3337930	3337980	3338030	3338080	3338130
	Mtz Trolley - 125 FPM VS		3337890	3337940	3337990	3338040	3338090	3338140
		B	36-7/8	38	36-7/8	36-7/8	40-1/4	39
		C	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8
H3	Lug		3338150	3338200	3338250	3338300	3338350	3338400
	Plain Trolley		3338160	3338210	3338260	3338310	3338360	3338410
	Geared Trolley		3338170	3338220	3338270	3338320	3338370	3338420
	Mtz Trolley - 65 FPM SS		3338180	3338230	3338280	3338330	3338380	3338430
	Mtz Trolley - 125 FPM VS		3338190	3338240	3338290	3338340	3338390	3338440
		B	41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
		C	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8

(a) Optional trolley brake.

All dimensions in inches.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.


TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Variable Speed
HP	1/2	1/2


WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

ALL LIFTS

Wheel Dia. 5




Straight track trolley




MOTORIZED TROLLEY



Wheel Dia. 5



Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING

3 TON

CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 5/16"

30-38

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control	22	22-7	22	30	30-10	30
		HP	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
H3 22	Lug		3350330	3350380	3350430	3350480	3350530	3350580
	Plain Trolley		3350340	3350390	3350440	3350490	3350540	3350590
	Geared Trolley		3350350	3350400	3350450	3350500	3350550	3350600
	Mtz Trolley - 65 FPM SS		3350360	3350410	3350460	3350510	3350560	3350610
	Mtz Trolley - 125 FPM VS		3350370	3350420	3350470	3350520	3350570	3350620
	B		30-3/8	31-1/2	30-3/8	30-3/8	33-3/4	32-1/2
	C		34-1/8	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8
	T ₁		8	8	8	8	8	8
	T ₂		7-3/4	7-3/4	7-3/4	7-3/4	7-3/4	7-3/4
H3 34	Lug		3350630	3350680	3350730	3350780	3350830	3350880
	Plain Trolley		3350640	3350690	3350740	3350790	3350840	3350890
	Geared Trolley		3350650	3350700	3350750	3350800	3350850	3350900
	Mtz Trolley - 65 FPM SS		3350660	3350710	3350760	3350810	3350860	3350910
	Mtz Trolley - 125 FPM VS		3350670	3350720	3350770	3350820	3350870	3350920
	B		33-7/8	35	33-7/8	33-7/8	37-1/4	36
	C		37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8
	T ₁		11-1/2	11-1/2	11-1/2	11-1/2	11-1/2	11-1/2
	T ₂		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
H3 45	Lug		3350930	3350980	3351030	3351080	3351130	3351180
	Plain Trolley		3350940	3350990	3351040	3351090	3351140	3351190
	Geared Trolley		3350950	3351000	3351050	3351100	3351150	3351200
	Mtz Trolley - 65 FPM SS		3350960	3351010	3351060	3351110	3351160	3351210
	Mtz Trolley - 125 FPM VS		3350970	3351020	3351070	3351120	3351170	3351220
	B		36-7/8	38	36-7/8	36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8
	T ₁		14-1/2	14-1/2	14-1/2	14-1/2	14-1/2	14-1/2
	T ₂		14-1/4	14-1/4	14-1/4	14-1/4	14-1/4	14-1/4
H3 60	Lug		3351230	3351280	3351330	3351380	3351430	3351480
	Plain Trolley		3351240	3351290	3351340	3351390	3351440	3351490
	Geared Trolley		3351250	3351300	3351350	3351400	3351450	3351500
	Mtz Trolley - 65 FPM SS		3351260	3351310	3351360	3351410	3351460	3351510
	Mtz Trolley - 125 FPM VS		3351270	3351320	3351370	3351420	3351470	3351520
	B		41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8
	T ₁		19	19	19	19	19	19
	T ₂		18-3/4	18-3/4	18-3/4	18-3/4	18-3/4	18-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-39 Issued 2-19-88



**CLOSE HEADROOM
PARALLEL MOUNTED**

2 PART DOUBLE REEVING - 5/16"

**3
TON**



Wheel Dia. 5

ALL LIFTS





MOTORIZED TROLLEY

Wheel Dia. 5



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

4 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 3/8"

30-40




PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	4	4—1-1/3	4
H3	15	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂	3230650 3230660 3230670 3230680 3230690 7-3/8 27-3/8 29-5/8 3 1/2	3230700 3230710 3230720 3230730 3230740 7-3/8 29-3/8 29-5/8 3 1/2	3230750 3230760 3230770 3230780 3230790 7-3/8 27-3/8 29-5/8 3 1/2
	20	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3230800 3230810 3230820 3230830 3230840 7-5/8 29-7/8 32-1/8 5-5/8 7/8 7-3/8 14-3/4	3230850 3230860 3230870 3230880 3230890 7-5/8 31-7/8 32-1/8 5-5/8 7/8 7-3/8 14-3/4	3230900 3230910 3230920 3230930 3230940 7-5/8 29-7/8 32-1/8 5-5/8 7/8 7-3/8 14-3/4
	26	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3230950 3230960 3230970 3230980 3230990 7-5/8 32-3/8 34-5/8 8 2 9-7/8 19-3/4	3231000 3231010 3231020 3231030 3231040 7-5/8 34-3/8 34-5/8 8 2 9-7/8 19-3/4	3231050 3231060 3231070 3231080 3231090 7-5/8 32-3/8 34-5/8 8 2 9-7/8 19-3/4
	31	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3231100 3231110 3231120 3231130 3231140 7-5/8 34-7/8 37-1/8 10-5/8 3-3/8 12-3/8 24-3/4	3231150 3231160 3231170 3231180 3231190 7-5/8 36-7/8 37-1/8 10-5/8 3-3/8 12-3/8 24-3/4	3231200 3231210 3231220 3231230 3231240 7-5/8 34-7/8 37-1/8 10-5/8 3-3/8 12-3/8 24-3/4
	44	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS A B C H ₁ H ₂ T ₁ T ₂	3231250 3231260 3231270 3231280 3231290 7-5/8 40-3/8 42-5/8 16 6 17-7/8 35-3/4	3231300 3231310 3231320 3231330 3231340 7-5/8 42-3/8 42-5/8 16 6 17-7/8 35-3/4	3231350 3231360 3231370 3231380 3231390 7-5/8 40-3/8 42-5/8 16 6 17-7/8 35-3/4

20, 26, 31, 44 FOOT LIFTS




15 FOOT LIFTS

Wheel Dia. 5





MOTORIZED TROLLEY

Wheel Dia. 5



PLAIN OR GEARED TROLLEY



LUG MOUNTING

Lift	Hoist Suspension	PRODUCT NUMBERS AND CLEARANCES		
		Lifting Speed	40-13	40
		Hoist Control	Two Speed	Variable Speed
	HP		10-3-1/3	10
H3	21	Lug	3432450	3432500
		Plain Trolley	3432460	3432510
		Geared Trolley	3432470	3432520
		Mtz Trolley - 65 FPM SS	3432480	3432530
		Mtz Trolley - 125 FPM VS	3432490	3432540
		A	11-1/4	11-1/4
		B	30-5/8	30-5/8
		C	28-7/8	28-7/8
		H ₁	2-1/2	2-1/2
		H ₂	1-1/2	1-1/2
H3	32	Lug	3432750	3432800
		Plain Trolley	3432760	3432810
		Geared Trolley	3432770	3432820
		Mtz Trolley - 65 FPM SS	3432780	3432830
		Mtz Trolley - 125 FPM VS	3432790	3432840
		A	11-1/4	11-1/4
		B	32-7/8	32-7/8
		C	31-1/8	31-1/8
		H ₁	4	4
		H ₂	2-1/8	2-1/8
H3	49	Lug	3433050	3433100
		Plain Trolley	3433060	3433110
		Geared Trolley	3433070	3433120
		Mtz Trolley - 65 FPM SS	3433080	3433130
		Mtz Trolley - 125 FPM VS	3433090	3433140
		A	10-7/8	10-7/8
		B	36-1/8	36-1/8
		C	34-3/8	34-3/8
		H ₁	7-1/4	7-1/4
		H ₂	2-1/8	2-1/8
H3	71	Lug	3433350	3433400
		Plain Trolley	3433360	3433410
		Geared Trolley	3433370	3433420
		Mtz Trolley - 65 FPM SS	3433380	3433430
		Mtz Trolley - 125 FPM VS	3433390	3433440
		A	10-7/8	10-7/8
		B	40-1/8	40-1/8
		C	38-3/8	38-3/8
		H ₁	11-1/4	11-1/4
		H ₂	2-1/8	2-1/8
H3	98	Lug	3433650	3433700
		Plain Trolley	3433660	3433710
		Geared Trolley	3433670	3433720
		Mtz Trolley - 65 FPM SS	3433680	3433730
		Mtz Trolley - 125 FPM VS	3433690	3433740
		A	10-7/8	10-7/8
		B	45-1/8	45-1/8
		C	43-3/8	43-3/8
		H ₁	16-1/4	16-1/4
		H ₂	2-1/8	2-1/8
H3	124	Lug	3433950	3434000
		Plain Trolley	3433960	3434010
		Geared Trolley	3433970	3434020
		Mtz Trolley - 65 FPM SS	3433980	3434030
		Mtz Trolley - 125 FPM VS	3433990	3434040
		A	10-7/8	10-7/8
		B	50-1/8	50-1/8
		C	48-3/8	48-3/8
		H ₁	21-1/4	21-1/4
		H ₂	2-1/8	2-1/8
H3		T ₁	21-3/8	21-3/8
		T ₂	42-3/4	42-3/4

All dimensions in inches.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 1/2"

30-44

PRODUCT NUMBERS AND CLEARANCES

Lift	Hoist Suspension	Lifting Speed	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2
H4	21	Lug	3432250	3432300	3432350
		Plain Trolley	3432260	3432310	3432360
		Geared Trolley	3432270	3432320	3432370
		Mtz Trolley - 65 FPM SS	3432280	3432330	3432380
		Mtz Trolley - 125 FPM VS	3432290	3432340	3432390
		B	24-5/8	28-3/4	24-3/4
		C	28-7/8	28-7/8	28-7/8
		H ₁	2-1/2	2-1/2	2-1/2
H4	32	H ₂	1-1/2	1-1/2	1-1/2
		Lug	3432550	3432600	3432650
		Plain Trolley	3432560	3432610	3432660
		Geared Trolley	3432570	3432620	3432670
		Mtz Trolley - 65 FPM SS	3432580	3432630	3432680
		Mtz Trolley - 125 FPM VS	3432590	3432640	3432690
		B	26-7/8	30-7/8	27
		C	31-1/8	31-1/8	31-1/8
H4	49	H ₁	4	4	4
		H ₂	2-1/8	2-1/8	2-1/8
		Lug	3432850	3432900	3432950
		Plain Trolley	3432860	3432910	3432960
		Geared Trolley	3432870	3432920	3432970
		Mtz Trolley - 65 FPM SS	3432880	3432930	3432980
		Mtz Trolley - 125 FPM VS	3432890	3432940	3432990
		B	30-1/8	34-1/8	30-1/4
H4	71	C	34-3/8	34-3/8	34-3/8
		H ₁	7-1/4	7-1/4	7-1/4
		H ₂	2-1/8	2-1/8	2-1/8
		T ₁	7-3/8	7-3/8	7-3/8
		T ₂	14-3/4	14-3/4	14-3/4
		Lug	3433150	3433200	3433250
		Plain Trolley	3433160	3433210	3433260
		Geared Trolley	3433170	3433220	3433270
H4	98	Mtz Trolley - 65 FPM SS	3433180	3433230	3433280
		Mtz Trolley - 125 FPM VS	3433190	3433240	3433290
		B	34-1/8	38-1/8	34-1/4
		C	38-3/8	38-3/8	38-3/8
		H ₁	11-1/4	11-1/4	11-1/4
		H ₂	2-1/8	2-1/8	2-1/8
		T ₁	11-3/8	11-3/8	11-3/8
		T ₂	22-3/4	22-3/4	22-3/4
H4	124	Lug	3433450	3433500	3433550
		Plain Trolley	3433460	3433510	3433560
		Geared Trolley	3433470	3433520	3433570
		Mtz Trolley - 65 FPM SS	3433480	3433530	3433580
		Mtz Trolley - 125 FPM VS	3433490	3433540	3433590
		B	39-1/8	43-1/8	39-1/4
		C	43-3/8	43-3/8	43-3/8
		H ₁	16-1/4	16-1/4	16-1/4
H4		H ₂	2-1/8	2-1/8	2-1/8
		T ₁	16-3/8	16-3/8	16-3/8
		T ₂	32-3/4	32-3/4	32-3/4
		Lug	3433750	3433800	3433850
		Plain Trolley	3433760	3433810	3433860
		Geared Trolley	3433770	3433820	3433870
		Mtz Trolley - 65 FPM SS	3433780	3433830	3433880
		Mtz Trolley - 125 FPM VS	3433790	3433840	3433890
H4		B	44-1/8	48-1/8	44-1/4
		C	48-3/8	48-3/8	48-3/8
		H ₁	21-1/4	21-1/4	21-1/4
		H ₂	2-1/8	2-1/8	2-1/8
		T ₁	21-3/8	21-3/8	21-3/8
		T ₂	42-3/4	42-3/4	42-3/4

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1

(a) Optional trolley brake,

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes and do not imply that lower flange of beam will support hoist with load.

All dimensions in inches.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-45 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**

2 PART SINGLE REEVING - 1/2"


**4
TON**

49, 71, 98, 124 FOOT LIFTS


21, 32 FOOT LIFTS

ALL LIFTS


Wheel Dia. 6



Straight track trolley




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 6






Straight track trolley



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

4 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 3/8"

30-46

Lift in Feet	Suspension	PRODUCT NUMBERS AND CLEARANCES			
		Lifting Speed	20	20-6	20
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	5	5-1-2/3	5
H3 27	Lug		3332300	3332350	3332400
	Plain Trolley		3332310	3332360	3332410
	Geared Trolley		3332320	3332370	3332420
	Mtz Trolley - 65 FPM SS		3332330	3332380	3332430
	Mtz Trolley - 125 FPM VS		3332340	3332390	3332440
	B		30-3/8	31-1/2	30-3/8
	C		34-1/8	34-1/8	34-1/8
	H ₁		5-3/4	5-3/4	5-3/4
	H ₂		3/4	3/4	3/4
	T ₁		8	8	8
	T ₂		7-3/4	7-3/4	7-3/4
H3 37	Lug		3332450	3332500	3332550
	Plain Trolley		3332460	3332510	3332560
	Geared Trolley		3332470	3332520	3332570
	Mtz Trolley - 65 FPM SS		3332480	3332530	3332580
	Mtz Trolley - 125 FPM VS		3332490	3332540	3332590
	B		33-7/8	35	33-7/8
	C		37-5/8	37-5/8	37-5/8
	H ₁		9-1/4	9-1/4	9-1/4
	H ₂		2-1/2	2-1/2	2-1/2
	T ₁		11-1/2	11-1/2	11-1/2
	T ₂		11-1/4	11-1/4	11-1/4
H3 45	Lug		3332600	3332650	3332700
	Plain Trolley		3332610	3332660	3332710
	Geared Trolley		3332620	3332670	3332720
	Mtz Trolley - 65 FPM SS		3332630	3332680	3332730
	Mtz Trolley - 125 FPM VS		3332640	3332690	3332740
	B		36-7/8	38	36-7/8
	C		40-5/8	40-5/8	40-5/8
	H ₁		12-1/4	12-1/4	12-1/4
	H ₂		4	4	4
	T ₁		14-1/2	14-1/2	14-1/2
	T ₂		14-1/4	14-1/4	14-1/4
H3 57	Lug		3332750	3332800	3332850
	Plain Trolley		3332760	3332810	3332860
	Geared Trolley		3332770	3332820	3332870
	Mtz Trolley - 65 FPM SS		3332780	3332830	3332880
	Mtz Trolley - 125 FPM VS		3332790	3332840	3332890
	B		41-3/8	42-1/2	41-3/8
	C		45-1/8	45-1/8	45-1/8
	H ₁		16-3/4	16-3/4	16-3/4
	H ₂		6-3/4	6-3/4	6-3/4
	T ₁		19	19	19
	T ₂		18-3/4	18-3/4	18-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width.

Beam size must be specified. Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



WRIGHT Work-rated ELECTRIC HOISTS


30-47 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED



4 PART SINGLE REEVING - 3/8"

4
TON



ALL LIFTS




MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING



WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

4
TON

**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 3/8"

30-48

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed					
		Hoist Control	30	30-10	30	40-13	40
		HP	Single Speed	Two Speed	Variable Speed	Two Speed	Variable Speed
			7-1/2	7-1/2-2-1/2	7-1/2	10-3-1/3	10
H3	Lug					3442650	3442700
	Plain Trolley					3442660	3442710
	Geared Trolley					3442670	3442720
	Mtz Trolley - 65 FPM SS					3442680	3442730
	Mtz Trolley - 125 FPM VS					3442690	3442740
	B					36-1/8	36-1/8
	C					34-3/8	34-3/8
H4	Lug		3442450	3442500	3442550		
	Plain Trolley		3442460	3442510	3442560		
	Geared Trolley		3442470	3442520	3442570		
	Mtz Trolley - 65 FPM SS		3442480	3442530	3442580		
	Mtz Trolley - 125 FPM VS		3442490	3442540	3442590		
	B		30-1/8	34-1/8	30-1/4		
	C		34-3/8	34-3/8	34-3/8		
H3	Lug					3442950	3443000
	Plain Trolley					3442960	3443010
	Geared Trolley					3442970	3443020
	Mtz Trolley - 65 FPM SS					3442980	3443030
	Mtz Trolley - 125 FPM VS					3442990	3443040
	B					40-1/8	40-1/8
	C					38-3/8	38-3/8
H4	Lug		3442750	3442800	3442850		
	Plain Trolley		3442760	3442810	3442860		
	Geared Trolley		3442770	3442820	3442870		
	Mtz Trolley - 65 FPM SS		3442780	3442830	3442880		
	Mtz Trolley - 125 FPM VS		3442790	3442840	3442890		
	B		34-1/8	38-1/8	34-1/4		
	C		38-3/8	38-3/8	38-3/8		
H3	Lug					3443250	3443300
	Plain Trolley					3443260	3443310
	Geared Trolley					3443270	3443320
	Mtz Trolley - 65 FPM SS					3443280	3443330
	Mtz Trolley - 125 FPM VS					3443290	3443340
	B					45-1/8	45-1/8
	C					43-3/8	43-3/8
H4	Lug		3443050	3443100	3443150		
	Plain Trolley		3443060	3443110	3443160		
	Geared Trolley		3443070	3443120	3443170		
	Mtz Trolley - 65 FPM SS		3443080	3443130	3443180		
	Mtz Trolley - 125 FPM VS		3443090	3443140	3443190		
	B		39-1/8	43-1/8	39-1/4		
	C		43-3/8	43-3/8	43-3/8		
H3	Lug					3443550	3443600
	Plain Trolley					3443560	3443610
	Geared Trolley					3443570	3443620
	Mtz Trolley - 65 FPM SS					3443580	3443630
	Mtz Trolley - 125 FPM VS					3443590	3443640
	B					50-1/8	50-1/8
	C					48-3/8	48-3/8
H4	Lug		3443350	3443400	3443450		
	Plain Trolley		3443360	3443410	3443460		
	Geared Trolley		3443370	3443420	3443470		
	Mtz Trolley - 65 FPM SS		3443380	3443430	3443480		
	Mtz Trolley - 125 FPM VS		3443390	3443440	3443490		
	B		44-1/8	48-1/8	44-1/4		
	C		48-3/8	48-3/8	48-3/8		

TROLLEY MOTOR DATA:



Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1

(a) Optional trolley brake. All dimensions are in inches.



Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

**4
TON****CLOSE HEADROOM
CROSS MOUNTED**

4 PART DOUBLE REEVING - 1/4"

30-50

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	20	20-6	20
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	5	5-1-2/3	5
20 H3	Lug		3338450	3338500	3338550
	Plain Trolley		3338460	3338510	3338560
	Geared Trolley		3338470	3338520	3338570
	Mtz Trolley - 65 FPM SS		3338480	3338530	3338580
	Mtz Trolley - 125 FPM VS		3338490	3338540	3338590
	B		33-7/8	35	33-7/8
	C		37-5/8	37-5/8	37-5/8
26 H3	Lug		3338600	3338650	3338700
	Plain Trolley		3338610	3338660	3338710
	Geared Trolley		3338620	3338670	3338720
	Mtz Trolley - 65 FPM SS		3338630	3338680	3338730
	Mtz Trolley - 125 FPM VS		3338640	3338690	3338740
	B		36-7/8	38	36-7/8
	C		40-5/8	40-5/8	40-5/8
35 H3	Lug		3338750	3338800	3338850
	Plain Trolley		3338760	3338810	3338860
	Geared Trolley		3338770	3338820	3338870
	Mtz Trolley - 65 FPM SS		3338780	3338830	3338880
	Mtz Trolley - 125 FPM VS		3338790	3338840	3338890
	B		41-3/8	42-1/2	41-3/8
	C		45-1/8	45-1/8	45-1/8

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1


(a) Optional trolley brake

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.


All reference to beam flange widths are for clearance purposes only and do **not** imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.


ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2
H4 20	Lug		3460960	3461010	3461060
	Plain Trolley		3460970	3461020	3461070
	Geared Trolley		3460980	3461030	3461080
	Mtz Trolley - 65 FPM SS		3460990	3461040	3461090
	Mtz Trolley - 125 FPM VS		3461000	3461050	3461100
	B		30-1/8	34-1/8	30-1/4
	C		34-3/8	34-3/8	34-3/8
	T ₁		7-3/8	7-3/8	7-3/8
	T ₂		14-3/4	14-3/4	14-3/4
H4 33	Lug		3461260	3461310	3461360
	Plain Trolley		3461270	3461320	3461370
	Geared Trolley		3461280	3461330	3461380
	Mtz Trolley - 65 FPM SS		3461290	3461340	3461390
	Mtz Trolley - 125 FPM VS		3461300	3461350	3461400
	B		34-1/8	38-1/8	34-1/4
	C		38-3/8	38-3/8	38-3/8
	T ₁		11-3/8	11-3/8	11-3/8
	T ₂		22-3/4	22-3/4	22-3/4
H4 49	Lug		3461560	3461610	3461660
	Plain Trolley		3461570	3461620	3461670
	Geared Trolley		3461580	3461630	3461680
	Mtz Trolley - 65 FPM SS		3461590	3461640	3461690
	Mtz Trolley - 125 FPM VS		3461600	3461650	3461700
	B		39-1/8	43-1/8	39-1/4
	C		43-3/8	43-3/8	43-3/8
	T ₁		16-3/8	16-3/8	16-3/8
	T ₂		32-3/4	32-3/4	32-3/4
H4 65	Lug		3461860	3461910	3461960
	Plain Trolley		3461870	3461920	3461970
	Geared Trolley		3461880	3461930	3461980
	Mtz Trolley - 65 FPM SS		3461890	3461940	3461990
	Mtz Trolley - 125 FPM VS		3461900	3461950	3462000
	B		44-1/8	48-1/8	44-1/4
	C		48-3/8	48-3/8	48-3/8
	T ₁		21-3/8	21-3/8	21-3/8
	T ₂		42-3/4	42-3/4	42-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1



(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS

Wheel Dia. 6





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

5 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 3/8"

30-54

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15	20	20-7	20
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
H3	17	Lug	3333050	3333100	3333150	3333200	3333250	3333300
		Plain Trolley	3333060	3333110	3333160	3333210	3333260	3333310
		Geared Trolley	3333070	3333120	3333170	3333220	3333270	3333320
		Mtz Trolley - 65 FPM SS	3333080	3333130	3333180	3333230	3333280	3333330
		Mtz Trolley - 125 FPM VS	3333090	3333140	3333190	3333240	3333290	3333340
		A	10-1/8	10-1/8	10-1/8	10-1/8	10-1/8	10-1/8
		B	26-5/8	27-3/4	26-5/8	26-5/8	30	28-3/4
		C	30-3/8	30-3/8	30-3/8	30-3/8	30-3/8	30-3/8
		H ₁	2	2	2	2	2	2
		H ₂	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4
H3	27	Lug	3333500	3333550	3333600	3333650	3333700	3333750
		Plain Trolley	3333510	3333560	3333610	3333660	3333710	3333760
		Geared Trolley	3333520	3333570	3333620	3333670	3333720	3333770
		Mtz Trolley - 65 FPM SS	3333530	3333580	3333630	3333680	3333730	3333780
		Mtz Trolley - 125 FPM VS	3333540	3333590	3333640	3333690	3333740	3333790
		A	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
		B	30-3/8	31-1/2	30-3/8	30-3/8	33-3/4	32-1/2
		C	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8	34-1/8
		H ₁	5-3/4	5-3/4	5-3/4	5-3/4	5-3/4	5-3/4
		H ₂	3/4	3/4	3/4	3/4	3/4	3/4
H3	37	Lug	3333950	3334000	3334050	3334100	3334150	3334200
		Plain Trolley	3333960	3334010	3334060	3334110	3334160	3334210
		Geared Trolley	3333970	3334020	3334070	3334120	3334170	3334220
		Mtz Trolley - 65 FPM SS	3333980	3334030	3334080	3334130	3334180	3334230
		Mtz Trolley - 125 FPM VS	3333990	3334040	3334090	3334140	3334190	3334240
		A	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
		B	33-7/8	35	33-7/8	33-7/8	37-1/4	36
		C	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8
		H ₁	9-1/4	9-1/4	9-1/4	9-1/4	9-1/4	9-1/4
		H ₂	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
H3	45	Lug	3334400	3334450	3334500	3334550	3334600	3334650
		Plain Trolley	3334410	3334460	3334510	3334560	3334610	3334660
		Geared Trolley	3334420	3334470	3334520	3334570	3334620	3334670
		Mtz Trolley - 65 FPM SS	3334430	3334480	3334530	3334580	3334630	3334680
		Mtz Trolley - 125 FPM VS	3334440	3334490	3334540	3334590	3334640	3334690
		A	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
		B	36-7/8	38	36-7/8	36-7/8	40-1/4	39
		C	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8
		H ₁	12-1/4	12-1/4	12-1/4	12-1/4	12-1/4	12-1/4
		H ₂	4	4	4	4	4	4
H3	57	Lug	3334850	3334900	3334950	3335000	3335050	3335100
		Plain Trolley	3334860	3334910	3334960	3335010	3335060	3335110
		Geared Trolley	3334870	3334920	3334970	3335020	3335070	3335120
		Mtz Trolley - 65 FPM SS	3334880	3334930	3334980	3335030	3335080	3335130
		Mtz Trolley - 125 FPM VS	3334890	3334940	3334990	3335040	3335090	3335140
		A	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4	9-3/4
		B	41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
		C	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8
		H ₁	16-3/4	16-3/4	16-3/4	16-3/4	16-3/4	16-3/4
		H ₂	6-3/4	6-3/4	6-3/4	6-3/4	6-3/4	6-3/4
H3		T ₁	19	19	19	19	19	19
		T ₂	18-3/4	18-3/4	18-3/4	18-3/4	18-3/4	18-3/4

TOP VALUE HOISTS

All dimensions in inches.

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)



WRIGHT Work-rated ELECTRIC HOISTS

30-55 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 3/8"


**5
TON**

27, 37, 45, 57 FOOT LIFTS


17 FOOT LIFT

ALL LIFTS


Wheel Dia. 6



Straight track trolley




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 6






Straight track trolley



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

5 TON

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 1/2"

H4

H3

30-56

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22			30		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2	10	10-3-1/3	10
21	Lug		3434050	3434100	3434150	3434200	3434250	3434300
	Plain Trolley		3434060	3434110	3434160	3434210	3434260	3434310
	Geared Trolley		3434070	3434120	3434170	3434220	3434270	3434320
	Mtz Trolley - 65 FPM SS		3434080	3434130	3434180	3434230	3434280	3434330
	Mtz Trolley - 125 FPM VS		3434090	3434140	3434190	3434240	3434290	3434340
	A		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	B		24-5/8	28-3/4	24-3/4	25-1/2	30-5/8	30-5/8
	C		28-7/8	28-7/8	28-7/8	28-7/8	28-7/8	28-7/8
	H ₁		2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
	H ₂		2-1/2	2-1/2	2-1/2	1-1/2	1-1/2	1-1/2
32	Lug		3434350	3434400	3434450	3434500	3434550	3434600
	Plain Trolley		3434360	3434410	3434460	3434510	3434560	3434610
	Geared Trolley		3434370	3434420	3434470	3434520	3434570	3434620
	Mtz Trolley - 65 FPM SS		3434380	3434430	3434480	3434530	3434580	3434630
	Mtz Trolley - 125 FPM VS		3434390	3434440	3434490	3434540	3434590	3434640
	A		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	B		26-7/8	30-7/8	27	27-3/4	32-7/8	32-7/8
	C		31-1/8	31-1/8	31-1/8	31-1/8	31-1/8	31-1/8
	H ₁		4	4	4	4	4	4
	H ₂		2-1/8	2-1/8	2-1/8	2-1/8	2-1/8	2-1/8
49	Lug		3434650	3434700	3434750	3434800	3434850	3434900
	Plain Trolley		3434660	3434710	3434760	3434810	3434860	3434910
	Geared Trolley		3434670	3434720	3434770	3434820	3434870	3434920
	Mtz Trolley - 65 FPM SS		3434680	3434730	3434780	3434830	3434880	3434930
	Mtz Trolley - 125 FPM VS		3434690	3434740	3434790	3434840	3434890	3434940
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		30-1/8	34-1/8	30-1/4	31	36-1/8	36-1/8
	C		34-3/8	34-3/8	34-3/8	34-3/8	34-3/8	34-3/8
	H ₁		7-1/4	7-1/4	7-1/4	7-1/4	7-1/4	7-1/4
	H ₂		2-1/8	2-1/8	2-1/8	2-1/8	2-1/8	2-1/8
71	Lug		3434950	3435000	3435050	3435100	3435150	3435200
	Plain Trolley		3434960	3435010	3435060	3435110	3435160	3435210
	Geared Trolley		3434970	3435020	3435070	3435120	3435170	3435220
	Mtz Trolley - 65 FPM SS		3434980	3435030	3435080	3435130	3435180	3435230
	Mtz Trolley - 125 FPM VS		3434990	3435040	3435090	3435140	3435190	3435240
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		34-1/8	38-1/8	34-1/4	35	40-1/8	40-1/8
	C		38-3/8	38-3/8	38-3/8	38-3/8	38-3/8	38-3/8
	H ₁		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	H ₂		2-1/8	2-1/8	2-1/8	2-1/8	2-1/8	2-1/8
98	Lug		3435250	3435300	3435350	3435400	3435450	3435500
	Plain Trolley		3435260	3435310	3435360	3435410	3435460	3435510
	Geared Trolley		3435270	3435320	3435370	3435420	3435470	3435520
	Mtz Trolley - 65 FPM SS		3435280	3435330	3435380	3435430	3435480	3435530
	Mtz Trolley - 125 FPM VS		3435290	3435340	3435390	3435440	3435490	3435540
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		39-1/8	43-1/8	39-1/4	40	45-1/8	45-1/8
	C		43-3/8	43-3/8	43-3/8	43-3/8	43-3/8	43-3/8
	H ₁		16-1/4	16-1/4	16-1/4	16-1/4	16-1/4	16-1/4
	H ₂		2-1/8	2-1/8	2-1/8	2-1/8	2-1/8	2-1/8
124	Lug		3435550	3435600	3435650	3435700	3435750	3435800
	Plain Trolley		3435560	3435610	3435660	3435710	3435760	3435810
	Geared Trolley		3435570	3435620	3435670	3435720	3435770	3435820
	Mtz Trolley - 65 FPM SS		3435580	3435630	3435680	3435730	3435780	3435830
	Mtz Trolley - 125 FPM VS		3435590	3435640	3435690	3435740	3435790	3435840
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		44-1/8	48-1/8	44-1/4	45	50-1/8	50-1/8
	C		48-3/8	48-3/8	48-3/8	48-3/8	48-3/8	48-3/8
	H ₁		21-1/4	21-1/4	21-1/4	21-1/4	21-1/4	21-1/4
	H ₂		2-1/8	2-1/8	2-1/8	2-1/8	2-1/8	2-1/8

All dimensions in inches.



**WRIGHT Work-rated
ELECTRIC HOISTS**
30-57 Issued 2-19-88


**STANDARD HEADROOM
PARALLEL MOUNTED**
2 PART SINGLE REEVING - 1/2"

**5
TON**


49, 71, 98, 124 FOOT LIFTS

21, 32, FOOT LIFTS


ALL LIFTS




Straight track trolley




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY






Straight track trolley



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

TROLLEY MOTOR DATA:

Speed
Control
HP

65 FPM
Single Speed
1/2

125 FPM
5 Step Var. Speed
1/2 (2 Required)

(a) Optional trolley brake

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE - 9/16"

30-58

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	40	40-13	40	50	60
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
176	Lug		3601260	3601310	3601360	3601410	3601460
	Plain Trolley		3601270	3601320	3601370	3601420	3601470
	Gearred Trolley		3601280	3601330	3601380	3601430	3601480
	Mtz Trolley - 65 FPM SS		3601290	3601340	3601390	3601440	3601490
	Mtz Trolley - 125 FPM VS		3601300	3601350	3601400	3601450	3601500
	B		53-1/2	54-3/8	54-3/8	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 Required)

(a) Optional trolley brake.

Controls - Position X on drawing represents the normal location of the control box when mounted at the factory, and the location recommended for field mounting. Dimension shown is approximate, and depends upon size and type of controls. Variable speed and multi-motor controls may require another control box, to be mounted on the side opposite position X.

Work-rated trolleys are available for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.**

These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**



30-59 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**



2 PART SINGLE REEVING - 9/16"

**5
TON**



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam size.

		PRODUCT NUMBERS AND CLEARANCES			
Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10
H4	35	Lug	3513200	3513250	3513300
	Plain Trolley	3513210	3513260	3513310	
	Geared Trolley	3513220	3513270	3513320	
	Mtz Trolley - 65 FPM SS	3513230	3513280	3513330	
	Mtz Trolley - 125 FPM VS	3513240	3513290	3513340	
	A	12	12	12	
	B	28-1/8	33-1/2	33-3/4	
	C	34-3/4	34-3/4	34-3/4	
	H ₁	3-1/2	3-1/2	3-1/2	
	H ₂	2-3/4	2-3/4	2-3/4	
	T ₁	2-3/4	2-3/4	2-3/4	
	T ₂	8-1/2	8-1/2	8-1/2	
	X	1-25/32	1-25/32	1-25/32	
H4	49	Lug	3513350	3513400	3513450
	Plain Trolley	3513360	3513410	3513460	
	Geared Trolley	3513370	3513420	3513470	
	Mtz Trolley - 65 FPM SS	3513380	3513430	3513480	
	Mtz Trolley - 125 FPM VS	3513390	3513440	3513490	
	A	12	12	12	
	B	30-3/8	36	36	
	C	37	37	37	
	H ₁	4-1/4	4-1/4	4-1/4	
	H ₂	4-3/8	4-3/8	4-3/8	
	T ₁	6-1/4	6-1/4	6-1/4	
	T ₂	9-1/2	9-1/2	9-1/2	
	X	2-1/32	2-1/32	2-1/32	
H4	77	Lug	3513500	3513550	3513600
	Plain Trolley	3513510	3513560	3513610	
	Geared Trolley	3513520	3513570	3513620	
	Mtz Trolley - 65 FPM SS	3513530	3513580	3513630	
	Mtz Trolley - 125 FPM VS	3513540	3513590	3513640	
	A	11-3/4	11-3/4	11-3/4	
	B	35-3/8	41	41	
	C	42	42	42	
	H ₁	11-1/8	11-1/8	11-1/8	
	H ₂	2-3/8	2-3/8	2-3/8	
	T ₁	11-1/4	11-1/4	11-1/4	
	T ₂	22-1/2	22-1/2	22-1/2	
	H4	107	Lug	3513650	3513700
Plain Trolley		3513660	3513710	3513760	
Geared Trolley		3513670	3513720	3513770	
Mtz Trolley - 65 FPM SS		3513680	3513730	3513780	
Mtz Trolley - 125 FPM VS		3513690	3513740	3513790	
A		11-3/4	11-3/4	11-3/4	
B		40-3/8	46	46	
C		47	47	47	
H ₁		16-1/4	16-1/4	16-1/4	
H ₂		2-3/8	2-3/8	2-3/8	
T ₁		16-1/4	16-1/4	16-1/4	
T ₂		32-1/2	32-1/2	32-1/2	
H4		142	Lug	3513800	3513850
	Plain Trolley	3513810	3513860	3513910	
	Geared Trolley	3513820	3513870	3513920	
	Mtz Trolley - 65 FPM SS	3513830	3513880	3513930	
	Mtz Trolley - 125 FPM VS	3513840	3513890	3513940	
	A	11-3/4	11-3/4	11-3/4	
	B	46-3/8	52	52	
	C	53	53	53	
	H ₁	22-1/4	22-1/4	22-1/4	
	H ₂	2-3/8	2-3/8	2-3/8	
	T ₁	22-1/4	22-1/4	22-1/4	
	T ₂	44-1/2	44-1/2	44-1/2	

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)

All dimensions in inches.

(a) Optional trolley brake.

*Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.*


All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

77, 107, 142 FOOT LIFTS

35, 49 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"






Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING

5 TON

CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 3/8"

30-62

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2
18 H3	Lug		3340250	3340300	3340350
	Plain Trolley		3340260	3340310	3340360
	Geared Trolley		3340270	3340320	3340370
	Mtz Trolley - 65 FPM SS		3340280	3340330	3340380
	Mtz Trolley - 125 FPM VS		3340290	3340340	3340390
	B		31-1/2	35-1/4	32-1/2
20 H4	C		34-1/8	34-1/8	34-1/8
	Lug		3443950	3444000	3444050
	Plain Trolley		3443960	3444010	3444060
	Geared Trolley		3443970	3444020	3444070
	Mtz Trolley - 65 FPM SS		3443980	3444030	3444080
	Mtz Trolley - 125 FPM VS		3443990	3444040	3444090
27 H3	B		30-1/8	34-1/8	30-1/4
	C		34-3/8	34-3/8	34-3/8
	Lug		3340550	3340600	3340650
	Plain Trolley		3340560	3340610	3340660
	Geared Trolley		3340570	3340620	3340670
	Mtz Trolley - 65 FPM SS		3340580	3340630	3340680
33 H4	Mtz Trolley - 125 FPM VS		3340590	3340640	3340690
	B		35	38-3/4	36
	C		37-5/8	37-5/8	37-5/8
	Lug		3444250	3444300	3444350
	Plain Trolley		3444260	3444310	3444360
	Geared Trolley		3444270	3444320	3444370
35 H3	Mtz Trolley - 65 FPM SS		3444280	3444330	3444380
	Mtz Trolley - 125 FPM VS		3444290	3444340	3444390
	B		34-1/8	38-1/8	34-1/4
	C		38-3/8	38-3/8	38-3/8
	Lug		3340850	3340900	3340950
	Plain Trolley		3340860	3340910	3340960
48 H3	Geared Trolley		3340870	3340920	3340970
	Mtz Trolley - 65 FPM SS		3340880	3340930	3340980
	Mtz Trolley - 125 FPM VS		3340890	3340940	3340990
	B		38	41-3/4	39
	C		40-5/8	40-5/8	40-5/8
	Lug		3341150	3341200	3341250
49 H4	Plain Trolley		3341160	3341210	3341260
	Geared Trolley		3341170	3341220	3341270
	Mtz Trolley - 65 FPM SS		3341180	3341230	3341280
	Mtz Trolley - 125 FPM VS		3341190	3341240	3341290
	B		42-1/2	46-1/4	43-1/2
	C		45-1/8	45-1/8	45-1/8
65 H4	Lug		3444550	3444600	3444650
	Plain Trolley		3444560	3444610	3444660
	Geared Trolley		3444570	3444620	3444670
	Mtz Trolley - 65 FPM SS		3444580	3444630	3444680
	Mtz Trolley - 125 FPM VS		3444590	3444640	3444690
	B		39-1/8	43-1/8	39-1/4
	C		43-3/8	43-3/8	43-3/8
	Lug		3444850	3444900	3444950
	Plain Trolley		3444860	3444910	3444960
	Geared Trolley		3444870	3444920	3444970
	Mtz Trolley - 65 FPM SS		3444880	3444930	3444980
	Mtz Trolley - 125 FPM VS		3444890	3444940	3444990
	B		44-1/8	48-1/8	44-1/4
	C		48-3/8	48-3/8	48-3/8

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

All dimensions in inches.

TOP VALUE HOISTS

(a) Optional trolley brake.


TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Variable Speed
HP	1/2	1/2 (2 required)

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.


All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

Wheel Dia. 5 H3
6 H4




Straight track trolley

ALL LIFTS




MOTORIZED TROLLEY


Wheel Dia. 5 H3
6 H4




Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING



5 TON

CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 3/8"

30-64

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10
H2	18	Lug	3340400	3340450	3340500
		Plain Trolley	3340410	3340460	3340510
		Geared Trolley	3340420	3340470	3340520
		Mtz Trolley - 65 FPM SS	3340430	3340480	3340530
		Mtz Trolley - 125 FPM VS	3340440	3340490	3340540
		B	33-1/4	36-3/8	36-3/8
H3	20	C	34-1/8	34-1/8	34-1/8
		Lug	3444100	3444150	3444200
		Plain Trolley	3444110	3444160	3444210
		Geared Trolley	3444120	3444170	3444220
		Mtz Trolley - 65 FPM SS	3444130	3444180	3444230
		Mtz Trolley - 125 FPM VS	3444140	3444190	3444240
H2	27	B	31	36-1/8	36-1/8
		C	34-3/8	34-3/8	34-3/8
		Lug	3340700	3340750	3340800
		Plain Trolley	3340710	3340760	3340810
		Geared Trolley	3340720	3340770	3340820
		Mtz Trolley - 65 FPM SS	3340730	3340780	3340830
H3	33	Mtz Trolley - 125 FPM VS	3340740	3340790	3340840
		B	36-3/4	39-7/8	39-7/8
		C	37-5/8	37-5/8	37-5/8
		Lug	3444400	3444450	3444500
		Plain Trolley	3444410	3444460	3444510
		Geared Trolley	3444420	3444470	3444520
H2	35	Mtz Trolley - 65 FPM SS	3444430	3444480	3444530
		Mtz Trolley - 125 FPM VS	3444440	3444490	3444540
		B	35	40-1/8	40-1/8
		C	38-3/8	38-3/8	38-3/8
		Lug	3341000	3341050	3341100
		Plain Trolley	3341010	3341060	3341110
H2	48	Geared Trolley	3341020	3341070	3341120
		Mtz Trolley - 65 FPM SS	3341030	3341080	3341130
		Mtz Trolley - 125 FPM VS	3341040	3341090	3341140
		B	39-3/4	42-7/8	42-7/8
		C	40-5/8	40-5/8	40-5/8
		Lug	3341300	3341350	3341400
H2	49	Plain Trolley	3341310	3341360	3341410
		Geared Trolley	3341320	3341370	3341420
		Mtz Trolley - 65 FPM SS	3341330	3341380	3341430
		Mtz Trolley - 125 FPM VS	3341340	3341390	3341440
		B	44-1/4	47-3/8	47-3/8
		C	45-1/8	45-1/8	45-1/8
H3	55	Lug	3444700	3444750	3444800
		Plain Trolley	3444710	3444760	3444810
		Geared Trolley	3444720	3444770	3444820
		Mtz Trolley - 65 FPM SS	3444730	3444780	3444830
		Mtz Trolley - 125 FPM VS	3444740	3444790	3444840
		B	40	45-1/8	45-1/8
H3	65	C	43-3/8	43-3/8	43-3/8
		Lug	3445000	3445050	3445100
		Plain Trolley	3445010	3445060	3445110
		Geared Trolley	3445020	3445070	3445120
		Mtz Trolley - 65 FPM SS	3445030	3445080	3445130
		Mtz Trolley - 125 FPM VS	3445040	3445090	3445140
H3		B	45	50-1/8	50-1/8
		C	48-3/8	48-3/8	48-3/8

All dimensions in inches.

(a) Optional trolley brake.


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:


Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Variable Speed
HP	1/2	1/2 (2 required)

Wheel Dia. 5 H2
6 H3




Straight track trolley

ALL LIFTS




MOTORIZED TROLLEY


Wheel Dia. 5 H2
6 H3




Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING





CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 7/16"

30-66

		PRODUCT NUMBERS AND CLEARANCES					
Lift in Feet	Hoist Suspension	Lifting Speed	40	40-13	40	50	60
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
84 H4	Lug		3602510	3602560	3602610	3602660	3602710
	Plain Trolley		3602520	3602570	3602620	3602670	3602720
	Geared Trolley		3602530	3602580	3602630	3602680	3602730
	Mtz Trolley - 65 FPM SS		3602540	3602590	3602640	3602690	3602740
	Mtz Trolley - 125 FPM VS		3602550	3602600	3602650	3602700	3602750
	B		53-1/2	54-3/8	54-3/4	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 Required)

(a) Optional trolley brake.

Depending upon the type of controls and the size of the control box required, controls may be mounted in various positions within the confines of the overall dimensions shown on the drawing.



Work-rated trolleys are available for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.**

These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

5 TON

CLOSE HEADROOM CROSS MOUNTED

4 PART DOUBLE REEVING - 5/16"

30-68

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control HP	15	15-5	15	20	20-7	20
			Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			5	5-1-2/3	5	6-1/4	6-1/4-2	6-1/4
16 H3	Lug		3339050	3339100	3339150	3339200	3339250	3339300
	Plain Trolley		3339060	3339110	3339160	3339210	3339260	3339310
	Geared Trolley		3339070	3339120	3339170	3339220	3339270	3339320
	Mtz Trolley - 65 FPM SS		3339080	3339130	3339180	3339230	3339280	3339330
	Mtz Trolley - 125 FPM VS		3339090	3339140	3339190	3339240	3339290	3339340
	B		33-7/8	35	33-7/8	33-7/8	37-1/4	36
21 H3	C		37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8
	Lug		3339500	3339550	3339600	3339650	3339700	3339750
	Plain Trolley		3339510	3339560	3339610	3339660	3339710	3339760
	Geared Trolley		3339520	3339570	3339620	3339670	3339720	3339770
	Mtz Trolley - 65 FPM SS		3339530	3339580	3339630	3339680	3339730	3339780
	Mtz Trolley - 125 FPM VS		3339540	3339590	3339640	3339690	3339740	3339790
28 H3	B		36-7/8	38	36-7/8	36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8	40-5/8	40-5/8	40-5/8
	Lug		3339950	3340000	3340050	3340100	3340150	3340200
	Plain Trolley		3339960	3340010	3340060	3340110	3340160	3340210
	Geared Trolley		3339970	3340020	3340070	3340120	3340170	3340220
	Mtz Trolley - 65 FPM SS		3339980	3340030	3340080	3340130	3340180	3340230
	Mtz Trolley - 125 FPM VS		3339990	3340040	3340090	3340140	3340190	3340240
	B		41-3/8	42-1/2	41-3/8	41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8	45-1/8	45-1/8	45-1/8

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)

(a) Optional trolley brake.


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.


WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

ALL LIFTS

Wheel Dia. 5




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY



Wheel Dia. 5



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

5
TON

**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 7/16"

30-70

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed					
		Hoist Control	30	30-10	30	40-13	40
		HP	Single Speed	Two Speed	Variable Speed	Two Speed	Variable Speed
			10	10-3-1/3	10	15-5	15
H3	Lug					3505600	3505650
	Plain Trolley					3505610	3505660
	Geared Trolley					3505620	3505670
	Mtz Trolley - 65 FPM SS					3505630	3505680
	Mtz Trolley - 125 FPM VS					3505640	3505690
	B					41	41
	C					42	42
H4	Lug		3513950	3514000	3514050		
	Plain Trolley		3513960	3514010	3514060		
	Geared Trolley		3513970	3514020	3514070		
	Mtz Trolley - 65 FPM SS		3513980	3514030	3514080		
	Mtz Trolley - 125 FPM VS		3513990	3514040	3514090		
	B		35-3/8	41	41		
	C		42	42	42		
H3	Lug					3505800	3505850
	Plain Trolley					3505810	3505860
	Geared Trolley					3505820	3505870
	Mtz Trolley - 65 FPM SS					3505830	3505880
	Mtz Trolley - 125 FPM VS					3505840	3505890
	B					46	46
	C					47	47
H4	Lug		3514100	3514150	3514200		
	Plain Trolley		3514110	3514160	3514210		
	Geared Trolley		3514120	3514170	3514220		
	Mtz Trolley - 65 FPM SS		3514130	3514180	3514230		
	Mtz Trolley - 125 FPM VS		3514140	3514190	3514240		
	B		40-3/8	46	46		
	C		47	47	47		
H3	Lug					3506000	3506050
	Plain Trolley					3506010	3506060
	Geared Trolley					3506020	3506070
	Mtz Trolley - 65 FPM SS					3506030	3506080
	Mtz Trolley - 125 FPM VS					3506040	3506090
	B					52	52
	C					53	53
H4	Lug		3514250	3514300	3514350		
	Plain Trolley		3514260	3514310	3514360		
	Geared Trolley		3514270	3514320	3514370		
	Mtz Trolley - 65 FPM SS		3514280	3514330	3514380		
	Mtx Trolley - 125 FPM VS		3514290	3514340	3514390		
	B		46-3/8	52	52		
	C		53	53	53		

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)

(a) Optional trolley brake.


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.


ALL LIFTS

Wheel Dia. 6




Straight track trolley

MOTORIZED TROLLEY






Wheel Dia. 6



Straight track trolley

PLAIN OR GEARED TROLLEY



LUG MOUNTING

5 TON

CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 3/8 "

30-72

H4

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed						
		Hoist Control	22	22-7	22	30	30-10	30
		HP	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
			7-1/2	7-1/2 - 2-1/2	7-1/2	10	10-3/13	10
20	Lug		3462160	3462210	3462260	3462310	3462360	3462410
	Plain Trolley		3462170	3462220	3462270	3462320	3462370	3462420
	Geared Trolley		3462180	3462230	3462280	3462330	3462380	3462430
	Mtz Trolley - 65 FPM SS		3462190	3462240	3462290	3462340	3462390	3462440
	Mtz Trolley - 125 FPM VS		3462200	3462250	3462300	3462350	3462400	3462450
	B		30-1/8	34-1/8	30-1/4	31	36-1/8	36-1/8
	C		34-3/8	34-3/8	34-3/8	34-3/8	34-3/8	34-3/8
	T ₁		7-3/8	7-3/8	7-3/8	7-3/8	7-3/8	7-3/8
	T ₂		14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4
33	Lug		3462460	3462510	3462560	3462610	3462660	3462710
	Plain Trolley		3462470	3462520	3462570	3462620	3462670	3462720
	Geared Trolley		3462480	3462530	3462580	3462630	3462680	3462730
	Mtz Trolley - 65 FPM SS		3462490	3462540	3462590	3462640	3462690	3462740
	Mtz Trolley - 125 FPM VS		3462500	3462550	3462600	3462650	3462700	3462750
	B		34-1/8	38-1/8	34-1/4	35	40-1/8	40-1/8
	C		38-3/8	38-3/8	38-3/8	38-3/8	38-3/8	38-3/8
	T ₁		11-3/8	11-3/8	11-3/8	11-3/8	11-3/8	11-3/8
	T ₂		22-3/4	22-3/4	22-3/4	22-3/4	22-3/4	22-3/4
49	Lug		3462760	3462810	3462860	3462910	3462960	3463010
	Plain Trolley		3462770	3462820	3462870	3462920	3462970	3463020
	Geared Trolley		3462780	3462830	3462880	3462930	3462980	3463030
	Mtz Trolley - 65 FPM SS		3462790	3462840	3462890	3462940	3462990	3463040
	Mtz Trolley - 125 FPM VS		3462800	3462850	3462900	3462950	3463000	3463050
	B		39-1/8	43-1/8	39-1/4	40	45-1/8	45-1/8
	C		43-3/8	43-3/8	43-3/8	43-3/8	43-3/8	43-3/8
	T ₁		16-3/8	16-3/8	16-3/8	16-3/8	16-3/8	16-3/8
	T ₂		32-3/4	32-3/4	32-3/4	32-3/4	32-3/4	32-3/4
65	Lug		3463060	3463110	3463160	3463210	3463260	3463310
	Plain Trolley		3463070	3463120	3463170	3463220	3463270	3463320
	Geared Trolley		3463080	3463130	3463180	3463230	3463280	3463330
	Mtz Trolley - 65 FPM SS		3463090	3463140	3463190	3463240	3463290	3463340
	Mtz Trolley - 125 FPM VS		3463100	3463150	3463200	3463250	3463300	3463350
	B		44-1/8	48-1/8	44-1/4	45	50-1/8	50-1/8
	C		48-3/8	48-3/8	48-3/8	48-3/8	48-3/8	48-3/8
	T ₁		21-3/8	21-3/8	21-3/8	21-3/8	21-3/8	21-3/8
	T ₂		42-3/4	42-3/4	42-3/4	42-3/4	42-3/4	42-3/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



WRIGHT Work-rated ELECTRIC HOISTS



30-73 Issued 2-19-88

CLOSE HEADROOM PARALLEL MOUNTED



2 PART DOUBLE REEVING - 3/8"

**5
TON**



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

**5
TON**

**CLOSE HEADROOM
PARALLEL MOUNTED**

2 PART DOUBLE REEVING - 7/16"

30-74

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30	40-13	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10	15-5	15
H3	30	Lug				3517510	3517560
		Plain Trolley				3517520	3517570
		Geared Trolley				3517530	3517580
		Mtz Trolley - 65 FPM SS				3517540	3517590
		Mtz Trolley - 125 FPM VS				3517550	3517600
		B				41	41
		C				42	42
H4	30	T ₁				11-1/4	11-1/4
		T ₂				22-1/2	22-1/2
		Lug	3517310	3517360	3517410		
		Plain Trolley	3517320	3517370	3517420		
		Geared Trolley	3517330	3517380	3517430		
		Mtz Trolley - 65 FPM SS	3517340	3517390	3517440		
		Mtz Trolley - 125 FPM VS	3517350	3517400	3517450		
H3	46	B	35-5/8	41	41		
		C	42	42	42		
		T ₁	11-1/4	11-1/4	11-1/4		
		T ₂	22-1/2	22-1/2	22-1/2		
		Lug				3517810	3517860
		Plain Trolley				3517820	3517870
		Geared Trolley				3517830	3517880
H4	46	Mtz Trolley - 65 FPM SS				3517840	3517890
		Mtz Trolley - 125 FPM VS				3517850	3517900
		B				46	46
		C				47	47
		T ₁				16-1/4	16-1/4
		T ₂				32-1/2	32-1/2
		Lug	3517610	3517660	3517710		
H3	67	Plain Trolley	3517620	3517670	3517720	3518110	3518160
		Geared Trolley	3517630	3517680	3517730	3518120	3518170
		Mtz Trolley - 65 FPM SS	3517640	3517690	3517740	3518130	3518180
		Mtz Trolley - 125 FPM VS	3517650	3517700	3517750	3518140	3518190
		B	40-3/8	46	46	3518150	3518200
		C	47	47	47	52	52
		T ₁	16-1/4	16-1/4	16-1/4	53	53
H4	67	T ₂	32-1/2	32-1/2	32-1/2	22-1/4	22-1/4
		Lug				44-1/2	44-1/2
		Plain Trolley	3517910	3517960	3518010		
		Geared Trolley	3517920	3517970	3518020		
		Mtz Trolley - 65 FPM SS	3517930	3517980	3518030		
		Mtz Trolley - 125 FPM VS	3517940	3517990	3518040		
		B	3517950	3518000	3518050		
H3	67	B	46-3/8	52	52		
		C	53	53	53		
		T ₁	22-1/4	22-1/4	22-1/4		
		T ₂	44-1/2	44-1/2	44-1/2		
		Lug					
		Plain Trolley					
		Geared Trolley					
H4	67	Mtz Trolley - 65 FPM SS					
		Mtz Trolley - 125 FPM VS					
		B					
		C					
		T ₁					
		T ₂					
		Lug					

All dimensions in inches.

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-75 Issued 2-19-88



**CLOSE HEADROOM
PARALLEL MOUNTED**

2 PART DOUBLE REEVING - 7/16"

**5
TON**



Wheel Dia. 6

ALL LIFTS





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

6 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 7/16"

30-76

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	6-1/4	6-1/4-2	6-1/4
H3 16	Lug		3335300	3335350	3335400
	Plain Trolley		3335310	3335360	3335410
	Geared Trolley		3335320	3335370	3335420
	Mtz Trolley - 65 FPM SS		3335330	3335380	3335430
	Mtz Trolley - 125 FPM VS		3335340	3335390	3335440
	A		10-1/8	10-1/8	10-1/8
	B		26-5/8	30	28-3/4
	C		30-3/8	30-3/8	30-3/8
	H ₁		2	2	2
	H ₂		1-1/4	1-1/4	1-1/4
H3 26	Lug		3335600	3335650	3335700
	Plain Trolley		3335610	3335660	3335710
	Geared Trolley		3335620	3335670	3335720
	Mtz Trolley - 65 FPM SS		3335630	3335680	3335730
	Mtz Trolley - 125 FPM VS		3335640	3335690	3335740
	A		9-3/4	9-3/4	9-3/4
	B		30-3/8	33-3/4	32-1/2
	C		34-1/8	34-1/8	34-1/8
	H ₁		5-3/4	5-3/4	5-3/4
	H ₂		3/4	3/4	3/4
H3 35	Lug		3335900	3335950	3336000
	Plain Trolley		3335910	3335960	3336010
	Geared Trolley		3335920	3335970	3336020
	Mtz Trolley - 65 FPM SS		3335930	3335980	3336030
	Mtz Trolley - 125 FPM VS		3335940	3335990	3336040
	A		9-3/4	9-3/4	9-3/4
	B		33-7/8	37-1/4	36
	C		37-5/8	37-5/8	37-5/8
	H ₁		9-1/4	9-1/4	9-1/4
	H ₂		2-1/2	2-1/2	2-1/2
H3 42	Lug		3336200	3336250	3336300
	Plain Trolley		3336210	3336260	3336310
	Geared Trolley		3336220	3336270	3336320
	Mtz Trolley - 65 FPM SS		3336230	3336280	3336330
	Mtz Trolley - 125 FPM VS		3336240	3336290	3336340
	A		9-3/4	9-3/4	9-3/4
	B		36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8
	H ₁		12-1/4	12-1/4	12-1/4
	H ₂		4	4	4
H3 54	Lug		3336500	3336550	3336600
	Plain Trolley		3336510	3336560	3336610
	Geared Trolley		3336520	3336570	3336620
	Mtz Trolley - 65 FPM SS		3336530	3336580	3336630
	Mtz Trolley - 125 FPM VS		3336540	3336590	3336640
	A		9-3/4	9-3/4	9-3/4
	B		41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8
	H ₁		16-3/4	16-3/4	16-3/4
	H ₂		6-3/4	6-3/4	6-3/4
H3	T ₁		19	19	19
	T ₂		18-3/4	18-3/4	18-3/4

All dimensions in inches.

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-77 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**


4 PART SINGLE REEVING - 7/16"

**6
TON**


26, 35, 42, 54 FOOT LIFTS

16 FOOT LIFTS


Wheel Dia. 6



Straight track trolley




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY


Wheel Dia. 6






Straight track trolley



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 5/8"

30-78

Lift in Feet	Hoist Suspension	Lifting Speed Hoist Control HP	PRODUCT NUMBERS AND CLEARANCES	
			40-13	40
			Two Speed	Variable Speed
			15-5	15
H3	29	Lug	3521060	3519110
		Plain Trolley	3521070	3519120
		Geared Trolley	3521080	3519130
		Mtz Trolley - 65 FPM SS	3521090	3519140
		Mtz Trolley - 125 FPM VS	3521100	3519150
		A	12	12
		B	33-1/2	33-1/2
		C	34-3/4	34-3/4
		H ₁	3-1/2	3-1/2
		H ₂	2-3/4	2-3/4
		T ₁	2-3/4	2-3/4
		T ₂	8-1/2	8-1/2
		X	1-25/32	1-25/32
H3	41	Lug	3519210	3519260
		Plain Trolley	3519220	3519270
		Geared Trolley	3519230	3519280
		Mtz Trolley - 65 FPM SS	3519240	3519290
		Mtz Trolley - 125 FPM VS	3519250	3519300
		A	12	12
		B	36	36
		C	37	37
		H ₁	4-1/4	4-1/4
		H ₂	4-3/8	4-3/8
		T ₁	6-1/4	6-1/4
		T ₂	9-1/2	9-1/2
		X	2-1/32	2-1/32
H3	65	Lug	3519360	3519410
		Plain Trolley	3519370	3519420
		Geared Trolley	3519380	3519430
		Mtz Trolley - 65 FPM SS	3519390	3519440
		Mtz Trolley - 125 FPM VS	3519400	3519450
		A	11-3/4	11-3/4
		B	41	41
		C	42	42
		H ₁	11-1/4	11-1/4
		H ₂	2-3/8	2-3/8
		T ₁	11-1/4	11-1/4
		T ₂	22-1/2	22-1/2
H3	90	Lug	3519510	3519560
		Plain Trolley	3519520	3519570
		Geared Trolley	3519530	3519580
		Mtz Trolley - 65 FPM SS	3519540	3519590
		Mtz Trolley - 125 FPM VS	3519550	3519600
		A	11-3/4	11-3/4
		B	46	46
		C	47	47
		H ₁	16-1/4	16-1/4
		H ₂	2-3/8	2-3/8
		T ₁	16-1/4	16-1/4
		T ₂	32-1/2	32-1/2
H3	120	Lug	3519660	3519710
		Plain Trolley	3519670	3519720
		Geared Trolley	3519680	3519730
		Mtz Trolley - 65 FPM SS	3519690	3519740
		Mtz Trolley - 125 FPM VS	3519700	3519750
		A	11-3/4	11-3/4
		B	52	52
		C	53	53
		H ₁	22-1/4	22-1/4
		H ₂	2-3/8	2-3/8
		T ₁	22-1/4	22-1/4
		T ₂	44-1/2	44-1/2

All dimensions in inches.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-79 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**

2 PART SINGLE REEVING - 5/8"




**6
TON**

65, 90, 120 FOOT LIFTS

29, 41 FOOT LIFTS




ALL LIFTS

Wheel Dia. 6






MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

6
TON

**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 7/16"

30-80

Lift in Feet	Hoist Suspension	Lifting Speed Hoist Control HP	PRODUCT NUMBERS AND CLEARANCES	
			40-13	40
			Two Speed	Variable Speed
			15-5	15
H3	Lug		3518260	3518310
	Plain Trolley		3518270	3518320
	Geared Trolley		3518280	3518330
	Mtz Trolley - 65 FPM SS		3518290	3518340
	Mtz Trolley - 125 FPM VS		3518300	3518350
	B		41	41
	C		42	42
H3	Lug		3518410	3518460
	Plain Trolley		3518420	3518470
	Geared Trolley		3518430	3518480
	Mtz Trolley - 65 FPM SS		3518440	3518490
	Mtz Trolley - 125 FPM VS		3518450	3518500
	B		46	46
	C		47	47
H3	Lug		3518560	3518610
	Plain Trolley		3518570	3518620
	Geared Trolley		3518580	3518630
	Mtz Trolley - 65 FPM SS		3518590	3518640
	Mtz Trolley - 125 FPM VS		3518600	3518650
	B		52	52
	C		53	53

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-81 Issued 2-19-88



**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 7/16"

**6
TON**



ALL LIFTS

Wheel Dia. 6





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING



CLOSE HEADROOM
CROSS MOUNTED

4 PART DOUBLE REEVING - 5/16"

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	6-1/4	6-1/4-2	6-1/4
H3 16	Lug		3341600	3341650	3341700
	Plain Trolley		3341610	3341660	3341710
	Geared Trolley -		3341620	3341670	3341720
	Mtz Trolley - 65 FPM SS		3341630	3341680	3341730
	Mtz Trolley - 125 FPM VS		3341640	3341690	3341740
	B		33-7/8	37-1/4	36
	C		37-5/8	37-5/8	37-5/8
H3 21	Lug		3341900	3341950	3342000
	Plain Trolley		3341910	3341960	3342010
	Geared Trolley		3341920	3341970	3342020
	Mtz Trolley - 65 FPM SS		3341930	3341980	3342030
	Mtz Trolley - 125 FPM VS		3341940	3341990	3342040
	B		36-7/8	40-1/4	39
	C		40-5/8	40-5/8	40-5/8
H3 28	Lug		3342200	3342250	3342300
	Plain Trolley		3342210	3342260	3342310
	Geared Trolley		3342220	3342270	3342320
	Mtz Trolley - 65 FPM SS		3342230	3342280	3342330
	Mtz Trolley - 125 FPM VS		3342240	3342290	3342340
	B		41-3/8	44-3/4	43-1/2
	C		45-1/8	45-1/8	45-1/8

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 7/16"

30-84

		PRODUCT NUMBERS AND CLEARANCES		
Lift in Feet	Hoist Suspension	Lifting Speed	40-13	40
		Hoist Control	Two Speed	Variable Speed
		HP	15-5	15
H3 30	Lug		3518710	3518760
	Plain Trolley		3518720	3518770
	Geared Trolley		3518730	3518780
	Mtz Trolley - 65 FPM SS		3518740	3518790
	Mtz Trolley - 125 FPM VS		3518750	3518800
	B		41	41
	C		42	42
	T ₁		11-1/4	11-1/4
	T ₂		22-1/2	22-1/2
H3 46	Lug		3518860	3518910
	Plain Trolley		3518870	3518920
	Geared Trolley		3518880	3518930
	Mtz Trolley - 65 FPM SS		3518890	3518940
	Mtz Trolley - 125 FPM VS		3518900	3518950
	B		46	46
	C		47	47
	T ₁		16-1/4	16-1/4
	T ₂		32-1/2	32-1/2
H3 67	Lug		3519010	3519060
	Plain Trolley		3519020	3519070
	Geared Trolley		3519030	3519080
	Mtz Trolley - 65 FPM SS		3519040	3519090
	Mtz Trolley - 125 FPM VS		3519050	3519100
	B		52	52
	C		53	53
	T ₁		22-1/4	22-1/4
	T ₂		44-1/2	44-1/2

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1/2	1/2 (2 required)

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-85 Issued 2-19-88



**CLOSE HEADROOM
PARALLEL MOUNTED**

2 PART DOUBLE REEVING - 7/16"

**6
TON**



ALL LIFTS

Wheel Dia. 6





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed			
		Hoist Control	20	20-7	20
		HP	Single Speed	Two Speed	Variable Speed
			10	10-3-1/3	10
H3	16	Lug	3436300	3436350	3436400
		Plain Trolley	3436310	3436360	3436410
		Geared Trolley	3436320	3436370	3436420
		Mtz Trolley - 65 FPM SS	3436330	3436380	3436430
		Mtz Trolley - 125 FPM VS	3436340	3436390	3436440
		A	11-1/4	11-1/4	11-1/4
		B	27-3/4	32-7/8	32-7/8
		C	31-1/8	31-1/8	31-1/8
		H ₁	2	2	2
		H ₂	1-1/8	1-1/8	1-1/8
H3	24	Lug	3436600	3436650	3436700
		Plain Trolley	3436610	3436660	3436710
		Geared Trolley	3436620	3436670	3436720
		Mtz Trolley - 65 FPM SS	3436630	3436680	3436730
		Mtz Trolley - 125 FPM VS	3436640	3436690	3436740
		A	10-7/8	10-7/8	10-7/8
		B	31	36-1/8	36-5/8
		C	34-3/8	34-3/8	34-3/8
		H ₁	5-1/8	5-1/8	5-1/8
		H ₂	1/2	1/2	1/2
H3	35	Lug	3436900	3436950	3437000
		Plain Trolley	3436910	3436960	3437010
		Geared Trolley	3436920	3436970	3437020
		Mtz Trolley - 65 FPM SS	3436930	3436980	3437030
		Mtz Trolley - 125 FPM VS	3436940	3436990	3437040
		A	10-7/8	10-7/8	10-7/8
		B	35	40-1/8	40-1/8
		C	38-3/8	38-3/8	38-3/8
		H ₁	9-3/8	9-3/8	9-3/8
		H ₂	2-1/2	2-1/2	2-1/2
H3	49	Lug	3437200	3437250	3437300
		Plain Trolley	3437210	3437260	3437310
		Geared Trolley	3437220	3437270	3437320
		Mtz Trolley - 65 FPM SS	3437230	3437280	3437330
		Mtz Trolley - 125 FPM VS	3437240	3437290	3437340
		A	10-7/8	10-7/8	10-7/8
		B	40	45-1/8	45-1/8
		C	43-3/8	43-3/8	43-3/8
		H ₁	14-1/4	14-1/4	14-1/4
		H ₂	5	5	5
H3	62	Lug	3437500	3437550	3437600
		Plain Trolley	3437510	3437560	3437610
		Geared Trolley	3437520	3437570	3437620
		Mtz Trolley - 65 FPM SS	3437530	3437580	3437630
		Mtz Trolley - 125 FPM VS	3437540	3437590	3437640
		A	10-7/8	10-7/8	10-7/8
		B	45	50-1/8	50-1/8
		C	48-3/8	48-3/8	48-3/8
		H ₁	19-1/4	19-1/4	19-1/4
		H ₂	7-1/2	7-1/2	7-1/2
H3		T ₁	21-3/8	21-3/8	21-3/8
		T ₂	42-3/4	42-3/4	42-3/4

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-87 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**

4 PART SINGLE REEVING - 1/2"


**7 1/2
TON**

24, 35, 49, 62 FOOT LIFTS

16 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"






Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30	30-10	30
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10	15	15-5	15
H3 29	Lug		3501750	3501800	3501850	3501900	3501950	3502000
	Plain Trolley		3501760	3501810	3501860	3501910	3501960	3502010
	Geared Trolley		3501770	3501820	3501870	3501920	3501970	3502020
	Mtz Trolley - 65 FPM SS		3501780	3501830	3501880	3501930	3501980	3502030
	Mtz Trolley - 125 FPM VS		3501790	3501840	3501890	3501940	3501990	3502040
	A		12	12	12	12	12	12
	B		28-1/8	33-1/2	33-1/2	30-1/4	33-1/2	33-1/2
	C		34-3/4	34-3/4	34-3/4	34-3/4	34-3/4	34-3/4
	H ₁		3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2
	H ₂		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
	T ₁		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
	T ₂		8-1/2	8-1/2	8-1/2	8-1/2	8-1/2	8-1/2
	X		1-25/32	1-25/32	1-25/32	1-25/32	1-25/32	1-25/32
H3 41	Lug		3502100	3502150	3502200	3502250	3502300	3502350
	Plain Trolley		3502110	3502160	3502210	3502260	3502310	3502360
	Geared Trolley		3502120	3502170	3502220	3502270	3502320	3502370
	Mtz Trolley - 65 FPM SS		3502130	3502180	3502230	3502280	3502330	3502380
	Mtz Trolley - 125 FPM VS		3502140	3502190	3502240	3502290	3502340	3502390
	A		12	12	12	12	12	12
	B		30-3/8	36	36	32-1/2	36	36
	C		37	37	37	37	37	37
	H ₁		4-1/4	4-1/4	4-1/4	4-1/4	4-1/4	4-1/4
	H ₂		4-3/8	4-3/8	4-3/8	4-3/8	4-3/8	4-3/8
	T ₁		6-1/4	6-1/4	6-1/4	6-1/4	6-1/4	6-1/4
	T ₂		9-1/2	9-1/2	9-1/2	9-1/2	9-1/2	9-1/2
	X		2-1/32	2-1/32	2-1/32	2-1/32	2-1/32	2-1/32
H3 65	Lug		3502450	3502500	3502550	3502600	3502650	3502700
	Plain Trolley		3502460	3502510	3502560	3502610	3502660	3502710
	Geared Trolley		3502470	3502520	3502570	3502620	3502670	3502720
	Mtz Trolley - 65 FPM SS		3502480	3502530	3502580	3502630	3502680	3502730
	Mtz Trolley - 125 FPM VS		3502490	3502540	3502590	3502640	3502690	3502740
	A		11-3/4	11-3/4	11-3/4	11-3/4	11-3/4	11-3/4
	B		35-3/8	41	41	37-1/2	41	41
	C		42	42	42	42	42	42
	H ₁		11-1/8	11-1/8	11-1/8	11-1/8	11-1/8	11-1/8
	H ₂		2-3/8	2-3/8	2-3/8	2-3/8	2-3/8	2-3/8
	T ₁		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	T ₂		22-1/2	22-1/2	22-1/2	22-1/2	22-1/2	22-1/2
H3 90	Lug		3502800	3502850	3502900	3502950	3503000	3503050
	Plain Trolley		3502810	3502860	3502910	3502960	3503010	3503060
	Geared Trolley		3502820	3502870	3502920	3502970	3503020	3503070
	Mtz Trolley - 65 FPM SS		3502830	3502880	3502930	3502980	3503030	3503080
	Mtz Trolley - 125 FPM VS		3502840	3502890	3502940	3502990	3503040	3503090
	A		11-3/4	11-3/4	11-3/4	11-3/4	11-3/4	11-3/4
	B		40-3/8	46	46	42-1/2	46	46
	C		47	47	47	47	47	47
	H ₁		16-1/4	16-1/4	16-1/4	16-1/4	16-1/4	16-1/4
	H ₂		2-3/8	2-3/8	2-3/8	2-3/8	2-3/8	2-3/8
	T ₁		16-1/4	16-1/4	16-1/4	16-1/4	16-1/4	16-1/4
	T ₂		32-1/2	32-1/2	32-1/2	32-1/2	32-1/2	32-1/2
H3 120	Lug		3503150	3503200	3503250	3503300	3503350	3503400
	Plain Trolley		3503160	3503210	3503260	3503310	3503360	3503410
	Geared Trolley		3503170	3503220	3503270	3503320	3503370	3503420
	Mtz Trolley - 65 FPM SS		3503180	3503230	3503280	3503330	3503380	3503430
	Mtz Trolley - 125 FPM VS		3503190	3503240	3503290	3503340	3503390	3503440
	A		11-3/4	11-3/4	11-3/4	11-3/4	11-3/4	11-3/4
	B		46-3/8	52	52	48-1/2	52	52
	C		53	53	53	53	53	53
	H ₁		22-1/4	22-1/4	22-1/4	22-1/4	22-1/4	22-1/4
	H ₂		2-3/8	2-3/8	2-3/8	2-3/8	2-3/8	2-3/8
	T ₁		22-1/4	22-1/4	22-1/4	22-1/4	22-1/4	22-1/4
	T ₂		44-1/2	44-1/2	44-1/2	44-1/2	44-1/2	44-1/2

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-89 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**

2 PART SINGLE REEVING - 5/8"


**7 1/2
TON**

65, 90, 120 FOOT LIFTS

29, 41 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"






Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING



STANDARD HEADROOM PARALLEL MOUNTED

2 PART SINGLE REEVING - 5/8"

30-90

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30	40	50
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
160	Lug		3606760	3606810	3606860	3606910	3606960
	Plain Trolley		3606770	3606820	3606870	3606920	3606970
	Geared Trolley		3606780	3606830	3606880	3606930	3606980
	Mtz Trolley - 65 FPM SS		3606790	3606840	3606890	3606940	3606990
	Mtz Trolley - 125 FPM VS		3606800	3606850	3606900	3606950	3607000
	B		53-1/2	54-3/8	54-3/4	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Controls - Position X on drawing represents the normal location of the control box when mounted at the factory, and the location recommended for field mounting. Dimension shown is approximate, and depends upon size and type of controls. Variable speed and multi-motor controls may require another control box, to be mounted on the side opposite position X.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**



30-91 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**



2 PART SINGLE REEVING - 5/8"

**7 1/2
TON**



ALL LIFTS



MOTORIZED TROLLEY



PLAIN TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15		
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2
H4 16	Lug		3436150	3436200	3436250
	Plain Trolley		3436160	3436210	3436260
	Geared Trolley		3436170	3436220	3436270
	Mtz Trolley - 65 FPM SS		3436180	3436230	3436280
	Mtz Trolley - 125 FPM VS		3436190	3436240	3436290
	A		11-1/4	11-1/4	11-1/4
	B		26-7/8	30-7/8	27
	C		31-1/8	31-1/8	31-1/8
	H ₁		2	2	2
	H ₂		1-1/8	1-1/8	1-1/8
H4 24	Lug		3435450	3436500	3436550
	Plain Trolley		3436460	3436510	3436560
	Geared Trolley		3436470	3436520	3436570
	Mtz Trolley - 65 FPM SS		3436480	3436530	3436580
	Mtz Trolley - 125 FPM VS		3436490	3436540	3436590
	A		10-7/8	10-7/8	10-7/8
	B		30-1/8	34-1/8	30-1/4
	C		34-3/8	34-3/8	34-3/8
	H ₁		5-1/8	5-1/8	5-1/8
	H ₂		1/2	1/2	1/2
H4 35	Lug		3436750	3436800	3436850
	Plain Trolley		3436760	3436810	3436860
	Geared Trolley		3436770	3436820	3436870
	Mtz Trolley - 65 FPM SS		3436780	3436830	3436880
	Mtz Trolley - 125 FPM VS		3436790	3436840	3436890
	A		10-7/8	10-7/8	10-7/8
	B		34-1/8	38-1/8	34-1/4
	C		38-3/8	38-3/8	38-3/8
	H ₁		9-3/8	9-3/8	9-3/8
	H ₂		2-1/2	2-1/2	2-1/2
H4 49	Lug		3437050	3437100	3437150
	Plain Trolley		3437060	3437110	3437160
	Geared Trolley		3437070	3437120	3437170
	Mtz Trolley - 65 FPM SS		3437080	3437130	3437180
	Mtz Trolley - 125 FPM VS		3437090	3437140	3437190
	A		10-7/8	10-7/8	10-7/8
	B		39-1/8	43-1/8	39-1/4
	C		43-3/8	43-3/8	43-3/8
	H ₁		14-1/4	14-1/4	14-1/4
	H ₂		5	5	5
H4 62	Lug		3437350	3437400	3437450
	Plain Trolley		3437360	3437410	3437460
	Geared Trolley		3437370	3437420	3437470
	Mtz Trolley - 65 FPM SS		3437380	3437430	3437480
	Mtz Trolley - 125 FPM VS		3437390	3437440	3437490
	A		10-7/8	10-7/8	10-7/8
	B		44-1/8	48-1/8	44-1/4
	C		48-3/8	48-3/8	48-3/8
	H ₁		19-1/4	19-1/4	19-1/4
	H ₂		7-1/2	7-1/2	7-1/2

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



WRIGHT Work-rated ELECTRIC HOISTS

30-93 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 1/2"


**7 1/2
TON**

24, 35, 49, 62 FOOT LIFTS

16 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"






Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22			30		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10	15	15-5	15
22 H2	Lug		3446950	3447000	3447050	3447100	3447150	3447200
	Plain Trolley		3446960	3447010	3447060	3447110	3447160	3447210
	Geared Trolley		3446970	3447020	3447070	3447120	3447170	3447220
	Mtz Trolley - 65 FPM SS		3446980	3447030	3447080	3447130	3447180	3447230
	Mtz Trolley - 125 FPM VS		3446990	3447040	3447090	3447140	3447190	3447240
	B		35	40-1/8	40-1/8	38-1/8	40-1/8	40-1/8
	C		38-3/8	38-3/8	38-3/8	38-3/8	38-3/8	38-3/8
35 H2	Lug		3447250	3447300	3447350	3447400	3447450	3447500
	Plain Trolley		3447260	3447310	3447360	3447410	3447460	3447510
	Geared Trolley		3447270	3447320	3447370	3447420	3447470	3447520
	Mtz Trolley - 65 FPM SS		3447280	3447330	3447380	3447430	3447480	3447530
	Mtz Trolley - 125 FPM VS		3447290	3447340	3447390	3447440	3447490	3447540
	B		40	45-1/8	45-1/8	43-1/8	45-1/8	45-1/8
	C		43-3/8	43-3/8	43-3/8	43-3/8	43-3/8	43-3/8
49 H2	Lug		3447550	3447600	3447650	3447700	3447750	3447800
	Plain Trolley		3447560	3447610	3447660	3447710	3447760	3447810
	Geared Trolley		3447570	3447620	3447670	3447720	3447770	3447820
	Mtz Trolley - 65 FPM SS		3447580	3447630	3447680	3447730	3447780	3447830
	Mtz Trolley - 125 FPM VS		3447590	3447640	3447690	3447740	3447790	3447840
	B		45	50-1/8	50-1/8	48-1/8	50-1/8	50-1/8
	C		48-3/8	48-3/8	48-3/8	48-3/8	48-3/8	48-3/8

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-95 Issued 2-19-88


**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 1/2"


**7 1/2
TON**

ALL LIFTS

Wheel Dia. 6




Straight track trolley




MOTORIZED TROLLEY



Wheel Dia. 6



Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30	30-10	30	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed	Variable Speed
		HP	10	10-3-1/3	10	15	15-5	15	20
24	Lug		3506150	3506200	3506250	3506300	3506350	3506400	3506450
	Plain Trolley		3506160	3506210	3506260	3506310	3506360	3506410	3506460
	Geared Trolley		3506170	3506220	3506270	3506320	3506370	3506420	3506470
	Mtz Trolley - 65 FPM SS		3506180	3506230	3506280	3506330	3506380	3506430	3506480
	Mtz Trolley - 125 FPM VS		3506190	3506240	3506290	3506340	3506390	3506440	3506490
	B		35-3/8	41	41	37-1/2	41	41	41
	C		42	42	42	42	42	42	42
39	Lug		3506500	3506550	3506600	3506650	3506700	3506750	3506800
	Plain Trolley		3506510	3506560	3506610	3506660	3506710	3506760	3506810
	Geared Trolley		3506520	3506570	3506620	3506670	3506720	3506770	3506820
	Mtz Trolley - 65 FPM SS		3506530	3506580	3506630	3506680	3506730	3506780	3506830
	Mtz Trolley - 125 FPM VS		3506540	3506590	3506640	3506690	3506740	3506790	3506840
	B		40-3/8	46	46	42-1/2	46	46	46
	C		47	47	47	47	47	47	47
56	Lug		3506850	3506900	3506950	3507000	3507050	3507100	3507150
	Plain Trolley		3506860	3506910	3506960	3507010	3507060	3507110	3507160
	Geared Trolley		3506870	3506920	3506970	3507020	3507070	3507120	3507170
	Mtz Trolley - 65 FPM SS		3506880	3506930	3506980	3507030	3507080	3507130	3507180
	Mtz Trolley - 125 FPM VS		3506890	3506940	3506990	3507040	3507090	3507140	3507190
	B		46-3/8	52	52	48-1/2	52	52	52
	C		53	53	53	53	53	53	53

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-97 Issued 2-19-88


**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 1/2"


**7 1/2
TON**

ALL LIFTS

Wheel Dia. 6




Straight track trolley




MOTORIZED TROLLEY



Wheel Dia. 6



Straight track trolley



PLAIN OR GEARED TROLLEY



LUG MOUNTING



CLOSE HEADROOM
CROSS MOUNTED
2 PART DOUBLE REEVING - 1/2"

30-98

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	30	30-10	30	40	50
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
78	Lug		3608010	3608060	3608110	3608160	3608210
	Plain Trolley		3608020	3608070	3608120	3608170	3608220
	Geared Trolley		3608030	3608080	3608130	3608180	3608230
	Mtz Trolley - 65 FPM SS		3608040	3608090	3608140	3608190	3608240
	Mtz Trolley- 125 FPM VS		3608050	3608100	3608150	3608200	3608250
	B		53-1/2	54-3/8	54-3/4	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Depending upon the type of controls and the size of the control box required, controls may be mounted in various positions within the confines of the overall dimensions shown on the drawing.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-99 Issued 2-19-88



**CLOSE HEADROOM
CROSS MOUNTED**

2 PART DOUBLE REEVING - 1/2"

**7 1/2
TON**



ALL LIFTS

Wheel Dia. 6





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed Hoist Control HP	PRODUCT NUMBERS AND CLEARANCES					
			15 Single Speed	15-5 Two Speed	15 Variable Speed	20 Single Speed	20-7 Two Speed	20 Variable Speed
			7-1/2	7-1/2-2-1/2	7-1/2	10	10-3-1/3	10
H3	Lug					3445600	3445650	3445700
	Plain Trolley					3445610	3445660	3445710
	Geared Trolley					3445620	3445670	3445720
	Mtz Trolley - 65 FPM SS					3445630	3445680	3445730
	Mtz Trolley - 125 FPM VS					3445640	3445690	3445740
	B					35	40-1/8	40-1/8
	C					38-3/8	38-3/8	38-3/8
H4	Lug		3445450	3445500	3445550			
	Plain Trolley		3445460	3445510	3445560			
	Geared Trolley		3445470	3445520	3445570			
	Mtz Trolley - 65 FPM SS		3445480	3445530	3445580			
	Mtz Trolley - 125 FPM VS		3445490	3445540	3445590			
	B		34-1/8	38-1/8	34-1/4			
	C		38-3/8	38-3/8	38-3/8			
H3	Lug					3445900	3445950	3446000
	Plain Trolley					3445910	3445960	3446010
	Geared Trolley					3445920	3445970	3446020
	Mtz Trolley - 65 FPM SS					3445930	3445980	3446030
	Mtz Trolley - 125 FPM VS					3445940	3445990	3446040
	B					40	45-1/8	45-1/8
	C					43-3/8	43-3/8	43-3/8
H4	Lug		3445750	3445800	3445850			
	Plain Trolley		3445760	3445810	3445860			
	Geared Trolley		3445770	3445820	3445870			
	Mtz Trolley - 65 FPM SS		3445780	3445830	3445880			
	Mtz Trolley - 125 FPM VS		3445790	3445840	3445890			
	B		39-1/8	43-1/8	39-1/4			
	C		43-3/8	43-3/8	43-3/8			
H3	Lug					3446200	3446250	3446300
	Plain Trolley					3446210	3446260	3446310
	Geared Trolley					3446220	3446270	3446320
	Mtz Trolley - 65 FPM SS					3446230	3446280	3446330
	Mtz Trolley - 125 FPM VS					3446240	3446290	3446340
	B					45	50-1/8	50-1/8
	C					48-3/8	48-3/8	48-3/8
H4	Lug		3446050	3446100	3446150			
	Plain Trolley		3446060	3446110	3446160			
	Geared Trolley		3446070	3446120	3446170			
	Mtz Trolley - 65 FPM SS		3446080	3446130	3446180			
	Mtz Trolley - 125 FPM VS		3446090	3446140	3446190			
	B		44-1/8	48-1/8	44-1/4			
	C		48-3/8	48-3/8	48-3/8			

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.


WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

ALL LIFTS

Wheel Dia. 6




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY



Wheel Dia. 6



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING



CLOSE HEADROOM PARALLEL MOUNTED

2 PART DOUBLE REEVING - 1/2"

30-102

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30	30-10	30	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed	Variable Speed
		HP	10	10-3-1/3	10	15	15-5	15	20
24	Lug		3519760	3519810	3519860	3519910	3519960	3520010	3520160
	Plain Trolley		3519770	3519820	3519870	3519920	3519970	3520020	3520170
	Geared Trolley		3519780	3519830	3519880	3519930	3519980	3520030	3520180
	Mtz Trolley - 65 FPM SS		3519790	3519840	3519890	3519940	3519990	3520040	3520190
	Mtz Trolley - 125 FPM VS		3519800	3519850	3519900	3519950	3520000	3520050	3520200
	B		35-5/8	41	41	37-1/2	41	41	41
	C		42	42	42	42	42	42	42
	T ₁		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	T ₂		22-1/2	22-1/2	22-1/2	22-1/2	22-1/2	22-1/2	22-1/2
39	Lug		3520210	3520260	3520310	3520360	3520410	3520460	3520610
	Plain Trolley		3520220	3520270	3520320	3520370	3520420	3520470	3520620
	Geared Trolley		3520230	3520280	3520330	3520380	3520430	3520480	3520630
	Mtz Trolley - 65 FPM SS		3520240	3520290	3520340	3520390	3520440	3520490	3520640
	Mtz Trolley - 125 FPM VS		3520250	3520300	3520350	3520400	3520450	3520500	3520650
	B		40-3/8	46	46	42-1/2	46	46	46
	C		47	47	47	47	47	47	47
	T ₁		16-1/4	16-1/4	16-1/4	16-1/4	16-1/4	16-1/4	16-1/4
	T ₂		32-1/2	32-1/2	32-1/2	32-1/2	32-1/2	32-1/2	32-1/2
56	Lug		3520660	3520710	3520760	3520810	3520860	3520910	3520960
	Plain Trolley		3520670	3520720	3520770	3520820	3520870	3520920	3520970
	Geared Trolley		3520680	3520730	3520780	3520830	3520880	3520930	3520980
	Mtz Trolley - 65 FPM SS		3520690	3520740	3520790	3520840	3520890	3520940	3520990
	Mtz Trolley - 125 FPM VS		3520700	3520750	3520800	3520850	3520900	3520950	3521000
	B		46-3/8	52	52	48-1/2	52	52	52
	C		53	53	53	53	53	53	53
	T ₁		22-1/4	22-1/4	22-1/4	22-1/4	22-1/4	22-1/4	22-1/4
	T ₂		44-1/2	44-1/2	44-1/2	44-1/2	44-1/2	44-1/2	44-1/2

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-103 Issued 2-19-88



**CLOSE HEADROOM
PARALLEL MOUNTED**

2 PART DOUBLE REEVING - 1/2"

**7 1/2
TON**



ALL LIFTS

Wheel Dia. 6





MOTORIZED TROLLEY

Wheel Dia. 6



PLAIN OR GEARED TROLLEY



LUG MOUNTING

10 TON

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 1/2"

30-104

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	20	20-7	20
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	15	15-5	15
H3 16	Lug		3437950	3438000	3438050
	Plain Trolley		3437960	3438010	3438060
	Geared Trolley		3437970	3438020	3438070
	Mtz Trolley - 65 FPM SS		3437980	3438030	3438080
	Mtz Trolley - 125 FPM VS		3437990	3438040	3438090
	A		11-1/4	11-1/4	11-1/4
	B		30-7/8	32-7/8	32-7/8
	C		31-1/8	31-1/8	31-1/8
	H ₁		2	2	2
	H ₂		1-1/8	1-1/8	1-1/8
H3 24	Lug		3438400	3438450	3438500
	Plain Trolley		3438410	3438460	3438510
	Geared Trolley		3438420	3438470	3438520
	Mtz Trolley - 65 FPM SS		3438430	3438480	3438530
	Mtz Trolley - 125 FPM VS		3438440	3438490	3438540
	A		10-7/8	10-7/8	10-7/8
	B		34-1/8	36-1/8	36-1/8
	C		34-3/8	34-3/8	34-3/8
	H ₁		5-1/8	5-1/8	5-1/8
	H ₂		1/2	1/2	1/2
H3 35	Lug		3438850	3438900	3438950
	Plain Trolley		3438860	3438910	3438960
	Geared Trolley		3438870	3438920	3438970
	Mtz Trolley - 65 FPM SS		3438880	3438930	3438980
	Mtz Trolley - 125 FPM VS		3438890	3438940	3438990
	A		10-7/8	10-7/8	10-7/8
	B		38-1/8	40-1/8	40-1/8
	C		38-3/8	38-3/8	38-3/8
	H ₁		9-3/8	9-3/8	9-3/8
	H ₂		2-1/2	2-1/2	2-1/2
H3 49	Lug		3439300	3439350	3439400
	Plain Trolley		3439310	3439360	3439410
	Geared Trolley		3439320	3439370	3439420
	Mtz Trolley - 65 FPM SS		3439330	3439380	3439430
	Mtz Trolley - 125 FPM VS		3439340	3439390	3439440
	A		10-7/8	10-7/8	10-7/8
	B		43-1/8	45-1/8	45-1/8
	C		43-3/8	43-3/8	43-3/8
	H ₁		14-1/4	14-1/4	14-1/4
	H ₂		5	5	5
H3 62	Lug		3439750	3439800	3439850
	Plain Trolley		3439760	3439810	3439860
	Geared Trolley		3439770	3439820	3439870
	Mtz Trolley - 65 FPM SS		3439780	3439830	3439880
	Mtz Trolley - 125 FPM VS		3439790	3439840	3439890
	A		10-7/8	10-7/8	10-7/8
	B		48-1/8	50-1/8	50-1/8
	C		48-3/8	48-3/8	48-3/8
	H ₁		19-1/4	19-1/4	19-1/4
	H ₂		7-1/2	7-1/2	7-1/2

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



WRIGHT Work-rated ELECTRIC HOISTS

30-105 Issued 2-19-88

STANDARD HEADROOM PARALLEL MOUNTED

4 PART SINGLE REEVING - 1/2"


10 TON

24, 35, 49, 62 FOOT LIFTS

16 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

H4

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	11	11-4	11	15	15-5	15
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2—2-1/2	7-1/2	10	10—3-1/3	10
16	Lug		3437650	3437700	3437750	3437800	3437850	3437900
	Plain Trolley		3437660	3437710	3437760	3437810	3437860	3437910
	Geared Trolley		3437670	3437720	3437770	3437820	3437870	3437920
	Mtz Trolley - 65 FPM SS		3437680	3437730	3437780	3437830	3437880	3437930
	Mtz Trolley - 125 FPM VS		3437690	3437740	3437790	3437840	3437890	3437940
	A		11-1/4	11-1/4	11-1/4	11-1/4	11-1/4	11-1/4
	B		26-7/8	30-7/8	27	27-3/4	32-7/8	32-7/8
	C		30-1/8	30-1/8	30-1/8	30-1/8	30-1/8	30-1/8
	H ₁		2	2	2	2	2	2
	H ₂		1-1/8	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8
24	Lug		3438100	3438150	3438200	3438250	3438300	3438350
	Plain Trolley		3438110	3438160	3438210	3438260	3438310	3438360
	Geared Trolley		3438120	3438170	3438220	3438270	3438320	3438370
	Mtz Trolley - 65 FPM SS		3438130	3438180	3438230	3438280	3438330	3438380
	Mtz Trolley - 125 FPM VS		3438140	3438190	3438240	3438290	3438340	3438390
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		30-1/8	34-1/8	30-1/4	31	36-1/8	36-1/8
	C		34-3/8	34-3/8	34-3/8	34-3/8	34-3/8	34-3/8
	H ₁		5-1/8	5-1/8	5-1/8	5-1/8	5-1/8	5-1/8
	H ₂		1/2	1/2	1/2	1/2	1/2	1/2
35	Lug		3438550	3438600	3438650	3438700	3438750	3438800
	Plain Trolley		3438560	3438610	3438660	3438710	3438760	3438810
	Geared Trolley		3438570	3438620	3438670	3438720	3438770	3438820
	Mtz Trolley - 65 FPM SS		3438580	3438630	3438680	3438730	3438780	3438830
	Mtz Trolley - 125 FPM VS		3438590	3438640	3438690	3438740	3438790	3438840
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		34-1/8	38-1/8	34-1/4	35	40-1/8	40-1/8
	C		38-3/8	38-3/8	38-3/8	38-3/8	38-3/8	38-3/8
	H ₁		9-3/8	9-3/8	9-3/8	9-3/8	9-3/8	9-3/8
	H ₂		2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
49	Lug		3439000	3439050	3439100	3439150	3439200	3439250
	Plain Trolley		3439010	3439060	3439110	3439160	3439210	3439260
	Geared Trolley		3439020	3439070	3439120	3439170	3439220	3439270
	Mtz Trolley - 65 FPM SS		3439030	3439080	3439130	3439180	3439230	3439280
	Mtz Trolley - 125 FPM VS		3439040	3439090	3439140	3439190	3439240	3439290
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		39-1/8	43-1/8	39-1/4	40	45-1/8	45-1/8
	C		43-3/8	43-3/8	43-3/8	43-3/8	43-3/8	43-3/8
	H ₁		14-1/4	14-1/4	14-1/4	14-1/4	14-1/4	14-1/4
	H ₂		5	5	5	5	5	5
62	Lug		3439450	3439500	3439550	3439600	3439650	3439700
	Plain Trolley	33	3439460	3439510	3439560	3439610	3439660	3439710
	Geared Trolley		3439470	3439520	3439570	3439620	3439670	3439720
	Mtz Trolley - 65 FPM SS		3439480	3439530	3439580	3439630	3439680	3439730
	Mtz Trolley - 125 FPM VS		3439490	3439540	3439590	3439640	3439690	3439740
	A		10-7/8	10-7/8	10-7/8	10-7/8	10-7/8	10-7/8
	B		44-1/8	48-1/8	44-1/4	45	50-1/8	50-1/8
	C		48-3/8	48-3/8	48-3/8	48-3/8	48-3/8	48-3/8
	H ₁		19-1/4	19-1/4	19-1/4	19-1/4	19-1/4	19-1/4
	H ₂		7-1/2	7-1/2	7-1/2	7-1/2	7-1/2	7-1/2

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width unless otherwise noted. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



**WRIGHT Work-rated
ELECTRIC HOISTS**

30-107 Issued 2-19-88

**STANDARD HEADROOM
PARALLEL MOUNTED**

4 PART SINGLE REEVING - 1/2"


**10
TON**

24, 35, 49, 62 FOOT LIFTS

16 FOOT LIFTS


ALL LIFTS

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"




MOTORIZED TROLLEY

Wheel Dia. 6




Straight track trolley

Minimum Flange Width 3-1/4"




Straight track trolley

Minimum Flange Width 4-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

**10
TON****STANDARD HEADROOM
PARALLEL MOUNTED**

2 PART SINGLE REEVING - 3/4"

30-108

H4**H3****H3****PRODUCT NUMBERS AND CLEARANCES**

Lift in Feet	Hoist Suspension	Lifting Speed	20*	20-10**	20*	30	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-7-1/2	15	20	25
32	Lug		3608260	3608310	3608360	3608410	3608460
	Plain Trolley		3608270	3608320	3608370	3608420	3608470
	Geared Trolley		3608280	3608330	3608380	3608430	3608480
	Mtz Trolley - 65 FPM SS		3608290	3608340	3608390	3608440	3608490
	Mtz Trolley - 125 FPM VS		3608300	3608350	3608400	3608450	3608500
	B		33-3/8	34-7/8	34-5/8	34-5/8	36-1/8
	C		38-1/4	38-1/4	38-1/4	38-1/4	38-1/4
	H ₁		6-3/8	6-3/8	6-3/8	6-3/8	6-3/8
	T ₂		40-1/2	40-1/2	40-1/2	40-1/2	40-1/2
46	Lug		3608510	3608560	3608610	3608660	3608710
	Plain Trolley		3608520	3608570	3608620	3608670	3608720
	Geared Trolley		3608530	3608580	3608630	3608680	3608730
	Mtz Trolley - 65 FPM SS		3608540	3608590	3608640	3608690	3608740
	Mtz Trolley - 125 FPM VS		3608550	3608600	3608650	3608700	3608750
	B		36-3/8	37-7/8	37-5/8	37-5/8	39-1/8
	C		41-1/4	41-1/4	41-1/4	41-1/4	41-1/4
	H ₁		9-3/8	9-3/8	9-3/8	9-3/8	9-3/8
	T ₂		46-1/2	46-1/2	46-1/2	46-1/2	46-1/2
60	Lug		3608760	3608810	3608860	3608910	3608960
	Plain Trolley		3608770	3608820	3608870	3608920	3608970
	Geared Trolley		3608780	3608830	3608880	3608930	3608980
	Mtz Trolley - 65 FPM SS		3608790	3608840	3608890	3608940	3608990
	Mtz Trolley - 125 FPM VS		3608800	3608850	3608900	3608950	3609000
	B		39-3/8	40-7/8	40-5/8	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
	H ₁		12-3/8	12-3/8	12-3/8	12-3/8	12-3/8
	T ₂		52-1/2	52-1/2	52-1/2	52-1/2	52-1/2
74	Lug		3609010	3609060	3609110	3609160	3609210
	Plain Trolley		3609020	3609070	3609120	3609170	3609220
	Geared Trolley		3609030	3609080	3609130	3609180	3609230
	Mtz Trolley - 65 FPM SS		3609040	3609090	3609140	3609190	3609240
	Mtz Trolley - 125 FPM VS		3609050	3609100	3609150	3609200	3609250
	B		42-3/8	43-7/8	43-5/8	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
	H ₁		15-3/8	15-3/8	15-3/8	15-3/8	15-3/8
	T ₂		58-1/2	58-1/2	58-1/2	58-1/2	58-1/2
102	Lug		3609260	3609310	3609360	3609410	3609460
	Plain Trolley		3609270	3609320	3609370	3609420	3609470
	Geared Trolley	3	3609280	3609330	3609380	3609430	3609480
	Mtz Trolley - 65 FPM SS		3609290	3609340	3609390	3609440	3609490
	Mtz Trolley - 125 FPM VS		3609300	3609350	3609400	3609450	3609500
	B		48-3/8	49-7/8	49-5/8	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
	H ₁		21-3/8	21-3/8	21-3/8	21-3/8	21-3/8
	T ₂		70-1/2	70-1/2	70-1/2	70-1/2	70-1/2
130	Lug		3609510	3609560	3609610	3609660	3609710
	Plain Trolley		3609520	3609570	3609620	3609670	3609720
	Geared Trolley		3609530	3609580	3609630	3609680	3609730
	Mtz Trolley - 65 FPM SS		3609540	3609590	3609640	3609690	3609740
	Mtz Trolley - 125 FPM VS		3609550	3609600	3609650	3609700	3609750
	B		54-3/8	55-7/8	55-5/8	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4
	H ₁		27-3/8	27-3/8	27-3/8	27-3/8	27-3/8
	T ₂		82-1/2	82-1/2	82-1/2	82-1/2	82-1/2

* 1200 RPM Hoist Motor ** 1200/600 RPM Hoist Motor

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

Minimum Radius Curve

Lift (Ft.)	32	46	60	74	102	130
Radius	78	90	114	114	138	156



Controls - Position X on drawing represents the normal location of the control box when mounted at the factory, and the location recommended for field mounting. Dimension shown is approximate, and depends upon size and type of controls. Variable speed and multi-motor controls may require another control box, to be mounted on the side opposite position X.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.**



These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam shown.

(a) Optional trolley brake.

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15
		Hoist Control	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10
H4 24	Lug		3514400	3514450	3514500
	Plain Trolley		3514410	3514460	3514510
	Geared Trolley		3514420	3514470	3514520
	Mtz Trolley - 65 FPM SS		3514430	3514480	3514530
	Mtz Trolley - 125 FPM VS		3514440	3514490	3514540
	B		30-3/8	36	36
	C		37	37	37
	H ₁		3-3/4	3-3/4	3-3/4
	H ₂		3/4	3/4	3/4
	T ₁		6-1/2	6-1/2	6-1/2
	T ₂		12-3/4	12-3/4	12-3/4
	T ₃		12-3/4	12-3/4	12-3/4
H4 39	Lug		3514550	3514600	3514650
	Plain Trolley		3514560	3514610	3514660
	Geared Trolley		3514570	3514620	3514670
	Mtz Trolley - 65 FPM SS		3514580	3514630	3514680
	Mtz Trolley - 125 FPM VS		3514590	3514640	3514690
	B		35-3/8	41	41
	C		42	42	42
	H ₁		8-1/2	8-1/2	8-1/2
	H ₂		1-3/4	1-3/4	1-3/4
	T ₁		11-1/4	11-1/4	11-1/4
	T ₂		21-3/4	21-3/4	21-3/4
	T ₃		16-3/4	16-3/4	16-3/4
H4 53	Lug		3514700	3514750	3514800
	Plain Trolley		3514710	3514760	3514810
	Geared Trolley		3514720	3514770	3514820
	Mtz Trolley - 65 FPM SS		3514730	3514780	3514830
	Mtz Trolley - 125 FPM VS		3514740	3514790	3514840
	B		40-3/8	46	46
	C		47	47	47
	H ₁		13-1/2	13-1/2	13-1/2
	H ₂		4-1/2	4-1/2	4-1/2
	T ₁		16-1/4	16-1/4	16-1/4
	T ₂		29-3/4	29-3/4	29-3/4
	T ₃		19	19	19
H4 71	Lug		3514850	3514900	3514950
	Plain Trolley		3514860	3514910	3514960
	Geared Trolley		3514870	3514920	3514970
	Mtz Trolley - 65 FPM SS		3514880	3514930	3514980
	Mtz Trolley - 125 FPM VS		3514890	3514940	3514990
	B		46-3/8	52	52
	C		53	53	53
	H ₁		19-1/2	19-1/2	19-1/2
	H ₂		7-1/2	7-1/2	7-1/2
	T ₁		22-1/4	22-1/4	22-1/4
	T ₂		38-3/4	38-3/4	38-3/4
	T ₃		19	19	19

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.


Work-rated trolleys are available for Standard I beam or WF beam, 5-7/16 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.


WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

ALL LIFTS

Wheel Dia. 6




Minimum Flange Width 5-7/16"




MOTORIZED TROLLEY


Wheel Dia. 6




Minimum Flange Width 5-7/16"



PLAIN OR GEARED TROLLEY



LUG MOUNTING



10 TON

CLOSE HEADROOM CROSS MOUNTED

2 PART DOUBLE REEVING - 1/2"

30-112

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	22	22-7	22	30
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20
24 H3	Lug		3507350	3507400	3507450	3507500
	Plain Trolley		3507360	3507410	3507460	3507510
	Geared Trolley		3507370	3507420	3507470	3507520
	Mtz Trolley - 65 FPM SS		3507380	3507430	3507480	3507530
	Mtz Trolley - 125 FPM VS		3507390	3507440	3507490	3507540
	B		37-1/2	41	41	41
	C		42	42	42	42
38 H3	Lug		3507550	3507600	3507650	3507700
	Plain Trolley		3507560	3507610	3507660	3507710
	Geared Trolley		3507570	3507620	3507670	3507720
	Mtz Trolley - 65 FPM SS		3507580	3507630	3507680	3507730
	Mtz Trolley - 125 FPM VS		3507590	3507640	3507690	3507740
	B		42-1/2	46	46	46
	C		47	47	47	47
56 H3	Lug		3507750	3507800	3507850	3507900
	Plain Trolley		3507760	3507810	3507860	3507910
	Geared Trolley		3507770	3507820	3507870	3507920
	Mtz Trolley - 65 FPM SS		3507780	3507830	3507880	3507930
	Mtz Trolley - 125 FPM VS		3507790	3507840	3507890	3507940
	B		48-1/2	52	52	52
	C		53	53	53	53

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.



Work-rated trolleys are available for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.**

Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	11	11-4	11	15	15-5	15	20	20-7	20
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	7-1/2	7-1/2-2-1/2	7-1/2	10	10-3-1/3	10	15	15-5	15
15	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C								3448450 3448500 3448550 3448460 3448510 3448560 3448470 3448520 3448570 3448480 3448530 3448580 3448490 3448540 3448590 38-1/8 40-1/8 40-1/8 38-3/8 38-3/8 38-3/8		
15	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C	3448150 3448200 3448250 3448160 3448210 3448260 3448170 3448220 3448270 3448180 3448230 3448280 3448190 3448240 3448290 34-1/8 38-1/8 34-1/4 38-3/8 38-3/8 38-3/8			3448300 3448350 3448400 3448310 3448360 3448410 3448320 3448370 3448420 3448330 3448380 3448430 3448340 3448390 3448440 35 40-1/8 40-1/8 38-3/8 38-3/8 38-3/8						
23	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C								3448900 3448950 3449000 3448910 3448960 3449010 3448920 3448970 3449020 3448930 3448980 3449030 3448940 3448990 3449040 43-1/8 45-1/8 45-1/8 43-3/8 43-3/8 43-3/8		
23	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C	3448600 3448650 3448700 3448610 3448660 3448710 3448620 3448670 3448720 3448630 3448680 3448730 3448640 3448690 3448740 39-1/8 43-1/8 39-1/4 43-3/8 43-3/8 43-3/8			3448750 3448800 3448850 3448760 3448810 3448860 3448770 3448820 3448870 3448780 3448830 3448880 3448790 3448840 3448890 40 45-1/8 45-1/8 43-3/8 43-3/8 43-3/8						
31	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C								3449350 3449400 3449450 3449360 3449410 3449460 3449370 3449420 3449470 3449380 3449430 3449480 3449390 3449440 3449490 48-1/8 50-1/8 50-1/8 48-3/8 48-3/8 48-3/8		
31	Lug Plain Trolley Geared Trolley Mtz Trolley - 65 FPM SS Mtz Trolley - 125 FPM VS B C	3449050 3449100 3449150 3449060 3449110 3449160 3449070 3449120 3449170 3449080 3449130 3449180 3449090 3449140 3449190 44-1/8 48-1/8 44-1/4 48-3/8 48-3/8 48-3/8			3449200 3449250 3449300 3449210 3449260 3449310 3449220 3449270 3449320 3449230 3449280 3449330 3449240 3449290 3449340 45 50-1/8 50-1/8 48-3/8 48-3/8 48-3/8						

All dimensions in inches.

TOP VALUE HOISTS

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.


WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

ALL LIFTS

Wheel Dia. 6




Curve track trolley - 78" Min. Radius




MOTORIZED TROLLEY



Wheel Dia. 6



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	20	20-10	20	30	40
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15 **	15-7-1/2***	15 **	20	25
15	Lug		3609760	3609810	3609860	3609910	3609960
	Plain Trolley		3609770	3609820	3609870	3609920	3609970
	Geared Trolley		3609780	3609830	3609880	3609930	3609980
	Mtz Trolley - 65 FPM SS		3609790	3609840	3609890	3609940	3609990
	Mtz Trolley - 125 FPM VS		3609800	3609850	3609900	3609950	3610000
	B		36-3/8	37-7/8	37-5/8	37-5/8	39-1/8
24	C		41-1/4	41-1/4	41-1/4	41-1/4	41-1/4
	Lug		3610010	3610060	3610110	3610160	3610210
	Plain Trolley		3610020	3610070	3610120	3610170	3610220
	Geared Trolley		3610030	3610080	3610130	3610180	3610230
	Mtz Trolley - 65 FPM SS		3610040	3610090	3610140	3610190	3610240
	Mtz Trolley - 125 FPM VS		3610050	3610100	3610150	3610200	3610250
34	B		39-3/8	40-7/8	40-5/8	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
	Lug		3610260	3610310	3610360	3610410	3610460
	Plain Trolley		3610270	3610320	3610370	3610420	3610470
	Geared Trolley		3610280	3610330	3610380	3610430	3610480
	Mtz Trolley - 65 FPM SS		3610290	3610340	3610390	3610440	3610490
52	Mtz Trolley - 125 FPM VS		3610300	3610350	3610400	3610450	3610500
	B		42-3/8	43-7/8	43-5/8	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
	Lug		3610510	3610560	3610610	3610660	3610710
	Plain Trolley		3610520	3610570	3610620	3610670	3610720
	Geared Trolley		3610530	3610580	3610630	3610680	3610730
71	Mtz Trolley - 65 FPM SS		3610540	3610590	3610640	3610690	3610740
	Mtz Trolley - 125 FPM VS		3610550	3610600	3610650	3610700	3610750
	B		48-3/8	49-7/8	49-5/8	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
	Lug		3610760	3610810	3610860	3610910	3610960
	Plain Trolley		3610770	3610820	3610870	3610920	3610970
	Geared Trolley		3610780	3610830	3610880	3610930	3610980
	Mtz Trolley - 65 FPM SS		3610790	3610840	3610890	3610940	3610990
	Mtz Trolley - 125 FPM VS		3610800	3610850	3610900	3610950	3611000
	B		54-3/8	55-7/8	55-5/8	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Trolley motor is positioned in this manner only on 15' & 24' lifts.

(b) Optional trolley brake.

Depending upon the type of controls and the size of the control box required, controls may be mounted in various positions within the confines of the overall dimensions shown on the drawing.

Work-rated trolleys are available for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

MINIMUM RADIUS CURVE FOR MOTORIZED TROLLEYS

Lift (Ft.)	15*	24*	34	52	71
Radius	None	None	138	138	138



* Recommended for straight track use only.

**1200 RPM hoist motor



***1200/600 RPM hoist motor

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



65 FPM AND 125 MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15			20		
		Hoist Control	Single Speed	Two Speed	Variable Speed	Single Speed	Two Speed	Variable Speed
		HP	10	10-3-1/3	10	15	15-5	15
H3	15	Lug				3515450	3515500	3515550
		Plain Trolley				3515460	3515510	3515560
		Geared Trolley				3515470	3515520	3515570
		Mtz Trolley - 65 FPM SS				3515480	3515530	3515580
		Mtz Trolley - 125 FPM VS				3515490	3515540	3515590
		B				37-1/2	41	41
H4	15	C				42	42	42
		Lug	3515000	3515050	3515100			
		Plain Trolley	3515010	3515060	3515110			
		Geared Trolley	3515020	3515070	3515120			
		Mtz Trolley - 65 FPM SS	3515030	3515080	3515130			
		Mtz Trolley - 125 FPM VS	3515040	3515090	3515140			
H3	23	B	35-3/8	41	41			
		C	42	42	42			
		Lug				3515600	3515650	3515700
		Plain Trolley				3515610	3515660	3515710
		Geared Trolley				3515620	3515670	3515720
		Mtz Trolley - 65 FPM SS				3515630	3515680	3515730
H4	23	Mtz Trolley - 125 FPM VS				3515640	3515690	3515740
		B	42-1/2	46	46			
		C	47	47	47			
		Lug	3515150	3515200	3515250			
		Plain Trolley	3515160	3515210	3515260			
		Geared Trolley	3515170	3515220	3515270			
H3	33	Mtz Trolley - 65 FPM SS	3515180	3515230	3515280			
		Mtz Trolley - 125 FPM VS	3515190	3515240	3515290			
		B	40-3/8	46	46			
		C	47	47	47			
		Lug				3515750	3515800	3515850
		Plain Trolley				3515760	3515810	3515860
H4	33	Geared Trolley				3515770	3515820	3515870
		Mtz Trolley - 65 FPM SS				3515780	3515830	3515880
		Mtz Trolley - 125 FPM VS				3515790	3515840	3515890
		B	48-1/2	52	52			
		C	53	53	53			
		Lug	3515300	3515350	3515400			
H3	33	Plain Trolley	3515310	3515360	3515410			
		Geared Trolley	3515320	3515370	3515420			
		Mtz Trolley - 65 FPM SS	3515330	3515380	3515430			
		Mtz Trolley - 125 FPM VS	3515340	3515390	3515440			
		B	46-3/8	52	52			
		C	53	53	53			

All dimensions in inches.

TROLLEY MOTOR DATA:


Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1	1 (2 Required)

(a) Optional trolley brake.


Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application. All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.


ALL LIFTS




Curve track trolley - 78" Min. Radius





MOTORIZED TROLLEY



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15	20
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20
H3 20	Lug		3515900	3515950	3516000	3504450
	Plain Trolley		3515910	3515960	3516010	3504460
	Geared Trolley		3515920	3515970	3516020	3504470
	Mtz Trolley - 65 FPM SS		3515930	3515980	3516030	3504480
	B		32-1/2	36	36	36
	C		37	37	37	37
	H ₁		3-3/4	3-3/4	3-3/4	3-3/4
	H ₂		3/4	3/4	3/4	3/4
	T ₁		6-1/4	6-1/4	6-1/4	6-1/4
	T ₂		12-3/4	12-3/4	12-3/4	12-3/4
	T ₃		12-3/4	12-3/4	12-3/4	12-3/4
H3 32	Lug		3516050	3516100	3516150	3504650
	Plain Trolley		3516060	3516110	3516160	3504660
	Geared Trolley		3516070	3516120	3516170	3504670
	Mtz Trolley - 65 FPM SS		3516080	3516130	3516180	3504680
	B		37-1/2	41	41	41
	C		42	42	42	42
	H ₁		8-1/2	8-1/2	8-1/2	8-1/2
	H ₂		1-3/4	1-3/4	1-3/4	1-3/4
	T ₁		11-1/4	11-1/4	11-1/4	11-1/4
	T ₂		21-3/4	21-3/4	21-3/4	21-3/4
	T ₃		16-3/4	16-3/4	16-3/4	16-3/4
H3 45	Lug		3516200	3516250	3516300	3504850
	Plain Trolley		3516210	3516260	3516310	3504860
	Geared Trolley		3516220	3516270	3516320	3504870
	Mtz Trolley - 65 FPM SS		3516230	3516280	3516330	3504880
	B		42-1/2	46	46	46
	C		47	47	47	47
	H ₁		13-1/2	13-1/2	13-1/2	13-1/2
	H ₂		4-1/2	4-1/2	4-1/2	4-1/2
	T ₁		16-1/4	16-1/4	16-1/4	16-1/4
	T ₂		29-3/4	29-3/4	29-3/4	29-3/4
	T ₃		19	19	19	19
H3 60	Lug		3516350	3516400	3516450	3505050
	Plain Trolley		3516360	3516410	3516460	3505060
	Geared Trolley		3516370	3516420	3516470	3505070
	Mtz Trolley - 65 FPM SS		3516380	3516430	3516480	3505080
	B		48-1/2	52	52	52
	C		53	53	53	53
	H ₁		19-1/2	19-1/2	19-1/2	19-1/2
	H ₂		7-1/2	7-1/2	7-1/2	7-1/2
	T ₁		22-1/4	22-1/4	22-1/4	22-1/4
	T ₂		38-3/4	38-3/4	38-3/4	38-3/4
	T ₃		19	19	19	19

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	1 (2 Required)	1 (2 Required)

(a) Optional trolley brake.



(b) 4-1/4 inches on 20 ft. lift and 5-1/2 inches on 32 and 45 foot lifts.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 5-7/16 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

**15
TON**
**STANDARD HEADROOM
PARALLEL MOUNTED**
 4 PART SINGLE REEVING - 5/8"

30-122

H4**H3****H3****PRODUCT NUMBERS AND CLEARANCES**

Lift in Feet	Hoist Suspension	Lifting Speed	15	15-5	15	20	25
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
20	Lug		3611010	3611060	3611110	3611160	3611210
	Plain Trolley		3611020	3611070	3611120	3611170	3611220
	Geared Trolley		3611030	3611080	3611130	3611180	3611230
	Mtz Trolley - 65 FPM SS		3611040	3611090	3611140	3611190	3611240
	Mtz Trolley - 125 FPM VS		3611050	3611100	3611150	3611200	3611250
	B		35-1/2	36-3/8	36-3/4	37-5/8	39-1/8
	C		41-1/4	41-1/4	41-1/4	41-1/4	41-1/4
	H ₁		3-7/8	3-7/8	3-7/8	3-7/8	3-7/8
	H ₃		3/4	3/4	3/4	3/4	3/4
	T ₂		49-1/2	49-1/2	49-1/2	49-1/2	49-1/2
28	Lug		3611260	3611310	3611360	3611410	3611460
	Plain Trolley		3611270	3611320	3611370	3611420	3611470
	Geared Trolley		3611280	3611330	3611380	3611430	3611480
	Mtz Trolley - 65 FPM SS		3611290	3611340	3611390	3611440	3611490
	Mtz Trolley - 125 FPM VS		3611300	3611350	3611400	3611450	3611500
	B		38-1/2	39-3/8	39-3/4	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
	H ₁		6-7/8	6-7/8	6-7/8	6-7/8	6-7/8
	H ₂		7/8	7/8	7/8	7/8	7/8
	T ₂		55-1/2	55-1/2	55-1/2	55-1/2	55-1/2
37	Lug		3611510	3611560	3611610	3611660	3611710
	Plain Trolley		3611520	3611570	3611620	3611670	3611720
	Geared Trolley		3611530	3611580	3611630	3611680	3611730
	Mtz Trolley - 65 FPM SS		3611540	3611590	3611640	3611690	3611740
	Mtz Trolley - 125 FPM VS		3611550	3611600	3611650	3611700	3611750
	B		41-1/2	42-3/8	42-3/4	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
	H ₁		9-7/8	9-7/8	9-7/8	9-7/8	9-7/8
	H ₂		2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
	T ₂		61-1/2	61-1/2	61-1/2	61-1/2	61-1/2
54	Lug		3611760	3611810	3611860	3611910	3611960
	Plain Trolley		3611770	3611820	3611870	3611920	3611970
	Geared Trolley		3611780	3611830	3611880	3611930	3611980
	Mtz Trolley - 65 FPM SS		3611790	3611840	3611890	3611940	3611990
	Mtz Trolley - 125 FPM VS		3611800	3611850	3611900	3611950	3612000
	B		47-1/2	48-3/8	48-3/4	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
	H ₁		15-7/8	15-7/8	15-7/8	15-7/8	15-7/8
	H ₂		5-7/8	5-7/8	5-7/8	5-7/8	5-7/8
	T ₂		73-1/2	73-1/2	73-1/2	73-1/2	73-1/2
71	Lug		3612010	3612060	3612110	3612160	3612210
	Plain Trolley		3612020	3612070	3612120	3612170	3612220
	Geared Trolley		3612030	3612080	3612130	3612180	3612230
	Mtz Trolley - 65 FPM SS		3612040	3612090	3612140	3612190	3612240
	Mtz Trolley - 125 FPM VS		3612050	3612100	3612150	3612200	3612250
	B		53-1/2	54-3/8	54-3/4	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4
	H ₁		21-7/8	21-7/8	21-7/8	21-7/8	21-7/8
	H ₂		9-1/8	9-1/8	9-1/8	9-1/8	9-1/8
	T ₂		85-1/2	85-1/2	85-1/2	85-1/2	85-1/2

All dimensions in inches.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

TROLLEY MOTOR DATA:

Minimum Radius Curve



Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	3/4 (2 Required)	1-1/2 (2 Required)

Lift (Ft.)	20	28	37	54	71
Radius	90	114	114	138	162



Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.

Controls - Position X on drawing represents the normal location of the control box when mounted at the factory, and the location recommended for field mounting. Dimension shown is approximate, and depends upon size and type of controls. Variable speed and multi-motor controls may require another control box, to be mounted on the side opposite position X.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING



CLOSE HEADROOM CROSS MOUNTED

4 PART DOUBLE REEVING - 1/2"

30-124

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed				
		Hoist Control HP	15	15-5	15	20
			Single Speed	Two Speed	Variable Speed	Variable Speed
			15	15-5	15	20
H3 19	Lug		3516500	3516550	3516600	3508100
	Plain Trolley		3516510	3516560	3516610	3508110
	Geared Trolley		3516520	3516570	3516620	3508120
	Mtz Trolley - 65 FPM SS		3516530	3516580	3516630	3508130
	B		42-1/2	46	46	46
	C		47	47	47	47
H3 28	Lug		3516650	3516700	3516750	3508300
	Plain Trolley		3516660	3516710	3516760	3508310
	Geared Trolley		3516670	3516720	3516770	3508320
	Mtz Trolley - 65 FPM SS		3516680	3516730	3516780	3508330
	B		48-1/2	52	52	52
	C		53	53	53	53

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM
Control	Single Speed
HP	1 (2 Required)


(a) Optional trolley brake.

Work-rated trolleys are adjustable for Standard I beam or WF beam, 4 inch to 8 inch flange width. **Beam size must be specified.** Trolleys are also available for 3.25 or 3.33" patented track beams. Trolleys for WF beams with flange widths greater than 8 inches available on application.


All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.


ALL LIFTS




Curve track trolley - 78" Min. Radius





MOTORIZED TROLLEY



Curve track trolley - 78" Min. Radius



PLAIN OR GEARED TROLLEY



LUG MOUNTING

**15
TON****CLOSE HEADROOM
CROSS MOUNTED**

4 PART DOUBLE REEVING - 1/2"

30-126

H4**H3****H3****PRODUCT NUMBERS AND CLEARANCES**

Lift in Feet	Hoist Suspension	Lifting Speed	15			20	
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15	15-5	15	20	25
15	Lug		3612260	3612310	3612360	3612410	3612460
	Plain Trolley		3612270	3612320	3612370	3612420	3612470
	Geared Trolley		3612280	3612330	3612380	3612430	3612480
	Mtz Trolley - 65 FPM SS		3612290	3612340	3612390	3612440	3612490
	Mtz Trolley - 125 FPM VS		3612300	3612350	3612400	3612450	3612500
	B		38-1/2	39-3/8	39-3/4	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
20	Lug		3612510	3612560	3612610	3612660	3612710
	Plain Trolley		3612520	3612570	3612620	3612670	3612720
	Geared Trolley		3612530	3612580	3612630	3612680	3612730
	Mtz Trolley - 65 FPM SS		3612540	3612590	3612640	3612690	3612740
	Mtz Trolley - 125 FPM VS		3612550	3612600	3612650	3612700	3612750
	B		41-1/2	42-3/8	42-3/4	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
30	Lug		3612760	3612810	3612860	3612910	3612960
	Plain Trolley		3612770	3612820	3612870	3612920	3612970
	Geared Trolley		3612780	3612830	3612880	3612930	3612980
	Mtz Trolley - 65 FPM SS		3612790	3612840	3612890	3612940	3612990
	Mtz Trolley - 125 FPM VS		3612800	3612850	3612900	3612950	3613000
	B		47-1/2	48-3/8	48-3/4	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
40	Lug	361	3613010	3613060	3613110	3613160	3613210
	Plain Trolley		3613020	3613070	3613120	3613170	3613220
	Geared Trolley		3613030	3613080	3613130	3613180	3613230
	Mtz Trolley - 65 FPM SS		3613040	3613090	3613140	3613190	3613240
	Mtz Trolley - 125 FPM VS		3613050	3613100	3613150	3613200	3613250
	B		53-1/2	54-3/8	54-3/4	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	3/4 (2 Required)	1-1/2 (2 Required)



Depending upon the type of controls and the size of the control box required, controls may be mounted in various positions within the confines of the overall dimensions shown on the drawing.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	10	10-5	10	15	20
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15 *	15-7-1/2 **	15 *	20	25
17	Lug		3613260	3613310	3613360	3613410	3613460
	Plain Trolley		3613270	3613320	3613370	3613420	3613470
	Geared Trolley		3613280	3613330	3613380	3613430	3613480
	Mtz Trolley - 65 FPM SS		3613290	3613340	3613390	3613440	3613490
	Mtz Trolley - 125 FPM VS		3613300	3613350	3613400	3613450	3613500
	B		39-3/8	40-7/8	40-5/8	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
	H ₁		6-3/8	6-3/8	6-3/8	6-3/8	6-3/8
	H ₂		1-3/8	1-3/8	1-3/8	1-3/8	1-3/8
	T ₂		55-1/2	55-1/2	55-1/2	55-1/2	55-1/2
24	Lug		3613510	3613560	3613610	3613660	3613710
	Plain Trolley		3613520	3613570	3613620	3613670	3613720
	Geared Trolley		3613530	3613580	3613630	3613680	3613730
	Mtz Trolley - 65 FPM SS		3613540	3613590	3613640	3613690	3613740
	Mtz Trolley - 125 FPM VS		3613550	3613600	3613650	3613700	3613750
	B		42-3/8	43-7/8	43-5/8	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
	H ₁		9-3/8	9-3/8	9-3/8	9-3/8	9-3/8
	H ₂		2-7/8	2-7/8	2-7/8	2-7/8	2-7/8
	T ₂		61-1/2	61-1/2	61-1/2	61-1/2	61-1/2
38	Lug		3613760	3613810	3613860	3613910	3613960
	Plain Trolley		3613770	3613820	3613870	3613920	3613970
	Geared Trolley		3613780	3613830	3613880	3613930	3613980
	Mtz Trolley - 65 FPM SS		3613790	3613840	3613890	3613940	3613990
	Mtz Trolley - 125 FPM VS		3613800	3613850	3613900	3613950	3614000
	B		48-3/8	49-7/8	49-5/8	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
	H ₁		15-3/8	15-3/8	15-3/8	15-3/8	15-3/8
	H ₂		6-1/4	6-1/4	6-1/4	6-1/4	6-1/4
	T ₂		73-1/2	73-1/2	73-1/2	73-1/2	73-1/2
52	Lug		3614010	3614060	3614110	3614160	3614210
	Plain Trolley		3614020	3614070	3614120	3614170	3614220
	Geared Trolley		3614030	3614080	3614130	3614180	3614230
	Mtz Trolley - 65 FPM SS		3614040	3614090	3614140	3614190	3614240
	Mtz Trolley - 125 FPM VS		3614050	3614100	3614150	3614200	3614250
	B		54-3/8	55-7/8	55-5/8	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4
	H ₁		21-3/8	21-3/8	21-3/8	21-3/8	21-3/8
	H ₂		9-3/8	9-3/8	9-3/8	9-3/8	9-3/8
	T ₂		85-1/2	85-1/2	85-1/2	85-1/2	85-1/2

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	3/4 (2 Required)	1-1/2 (2 Required)

Minimum Radius Curve

Lift (Ft.)	17	24	38	52
Radius	114	114	138	162

WARNING: Equipment described herein is not designed for, and should not be used for lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

Controls - Position X on drawing represents the normal location of the control box when mounted at the factory, and the location recommended for field mounting. Dimension shown is approximate, and depends upon size and type of controls. Variable speed and multi-motor controls may require another control box, to be mounted on the side opposite position X.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

* 1200 RPM hoist motor

** 1200/600 RPM hoist motor



ALL LIFTS

Wheel Dia. 8





MOTORIZED TROLLEY

Wheel Dia. 8



PLAIN OR GEARED TROLLEY



LUG MOUNTING

H4

H3

H3

PRODUCT NUMBERS AND CLEARANCES

Lift in Feet	Hoist Suspension	Lifting Speed	10	10-5	10	15	20
		Hoist Control	Single Speed	Two Speed	Variable Speed	Variable Speed	Variable Speed
		HP	15 *	15-7-1/2 **	15 *	20	25
13	Lug		3614260	3614310	3614360	3614410	3614460
	Plain Trolley		3614270	3614320	3614370	3614420	3614470
	Geared Trolley		3614280	3614330	3614380	3614430	3614480
	Mtz Trolley - 65 FPM SS		3614290	3614340	3614390	3614440	3614490
	Mtz Trolley - 125 FPM VS		3614300	3614350	3614400	3614450	3614500
	B		39-3/8	40-7/8	40-5/8	40-5/8	42-1/8
	C		44-1/4	44-1/4	44-1/4	44-1/4	44-1/4
18	Lug		3614510	3614560	3614610	3614660	3614710
	Plain Trolley		3614520	3614570	3614620	3614670	3614720
	Geared Trolley		3614530	3614580	3614630	3614680	3614730
	Mtz Trolley - 65 FPM SS		3614540	3614590	3614640	3614690	3614740
	Mtz Trolley - 125 FPM VS		3614550	3614600	3614650	3614700	3614750
	B		42-3/8	43-7/8	43-5/8	43-5/8	45-1/8
	C		47-1/4	47-1/4	47-1/4	47-1/4	47-1/4
27	Lug		3614760	3614810	3614860	3614910	3614960
	Plain Trolley		3614770	3614820	3614870	3614920	3614970
	Geared Trolley		3614780	3614830	3614880	3614930	3614980
	Mtz Trolley - 65 FPM SS		3614790	3614840	3614890	3614940	3614990
	Mtz Trolley - 125 FPM VS		3614800	3614850	3614900	3614950	3615000
	B		48-3/8	49-7/8	49-5/8	49-5/8	51-1/8
	C		53-1/4	53-1/4	53-1/4	53-1/4	53-1/4
37	Lug		3615010	3615060	3615110	3615160	3615210
	Plain Trolley		3615020	3615070	3615120	3615170	3615220
	Geared Trolley		3615030	3615080	3615130	3615180	3615230
	Mtz Trolley - 65 FPM SS		3615040	3615090	3615140	3615190	3615240
	Mtz Trolley - 125 FPM VS		3615050	3615100	3615150	3615200	3615250
	B		54-3/8	55-7/8	55-5/8	55-5/8	57-1/8
	C		59-1/4	59-1/4	59-1/4	59-1/4	59-1/4

All dimensions in inches.

TROLLEY MOTOR DATA:

Speed	65 FPM	125 FPM
Control	Single Speed	5 Step Var. Speed
HP	3/4 (2 Required)	1-1/2 (2 Required)

Depending upon the type of controls and the size of the control box required, controls may be mounted in various positions within the confines of the overall dimensions shown on the drawing.

Work-rated trolleys are available for Standard I beam or WF beam, 4-5/8 inch to 8 inch flange width. **Beam size must be specified.** These trolleys are not adjustable. Trolleys for WF beams with flange widths greater than 8 inches available on application.



All reference to beam flange widths are for clearance purposes only and do not imply that lower flange of beam will support hoist with load.

*1200 RPM hoist motor



**1200/600 RPM hoist motor

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.



ALL LIFTS



MOTORIZED TROLLEY



PLAIN OR GEARED TROLLEY



LUG MOUNTING

WARNING: Equipment described herein is not designed for, and should not be used for, lifting, supporting, or transporting humans. Modifications to upgrade, rerate, or otherwise alter the hoist equipment shall be authorized only by the original manufacturer or qualified professional engineer. Failure to comply with any one of the limitations noted herein may result in serious bodily injury.

See facing page for additional dimensions. All dimensions shown in inches. Dimensions which change with beam size are for minimum beam size.



Acco Chain & Lifting Products Division

A member of the Acco Material Handling Group

76 Acco Drive, P.O. Box 792, York, PA 17405
Telephone 717 741-4863
FAX 717 741-4956 Telex 84-0412

12140 Bellflower Blvd., Downey, CA 90241
Telephone 213 862-8101
FAX 213 862-4382

© Acco 1988
288 5M AP
Printed in U.S.A.